



# The Sizewell C Project

## 6.4 Volume 3 Northern Park and Ride Chapter 5 Air Quality

---

Revision: 1.0  
Applicable Regulation: Regulation 5(2)(a)  
PINS Reference Number: EN010012

---

May 2020

Planning Act 2008  
Infrastructure Planning (Applications: Prescribed  
Forms and Procedure) Regulations 2009



## Contents

5.	Air Quality .....	1
5.1	Introduction .....	1
5.2	Legislation, policy, and guidance .....	1
5.3	Methodology .....	3
5.4	Baseline environment .....	14
5.5	Environmental design and mitigation .....	17
5.6	Assessment .....	19
5.7	Mitigation and monitoring .....	27
5.8	Residual effects .....	27
	References .....	29

## Tables

Table 5.1:	Assessment of the value or sensitivity of receptors for air quality.....	6
Table 5.2:	Dust emission magnitude classification. ....	7
Table 5.3:	Risk of dust impacts – demolition. ....	8
Table 5.4:	Risk of dust impacts – earthworks and construction.....	9
Table 5.5:	Risk of dust impacts – trackout. ....	9
Table 5.6:	Assessment of transport emission magnitude of impact on air quality.....	10
Table 5.7:	Effect descriptors for annual mean NO <sub>2</sub> and PM <sub>10</sub> .....	11
Table 5.8:	Effect descriptors for annual mean PM <sub>2.5</sub> .....	11
Table 5.9:	NO <sub>2</sub> , PM <sub>10</sub> and PM <sub>2.5</sub> Concentrations for the Baseline Year 2018 at nearby Sensitive Receptors.....	15
Table 5.10:	NO <sub>2</sub> , PM <sub>10</sub> and PM <sub>2.5</sub> concentrations for the baseline year 2023 at nearby sensitive receptors.....	16
Table 5.11:	NO <sub>2</sub> , PM <sub>10</sub> and PM <sub>2.5</sub> concentrations for the baseline year 2028 at nearby sensitive receptors.....	16
Table 5.12:	Potential risk of dust impacts from activities without applied mitigation. ....	19
Table 5.13:	NO <sub>2</sub> Concentration for construction phase year 2023 and the magnitude of change compared to the 2023 baseline concentration. ....	20
Table 5.14:	PM <sub>10</sub> Concentration for construction phase year 2023 and the magnitude of change compared to the 2023 baseline concentration. ....	21

Table 5.15: PM<sub>2.5</sub> Concentration for construction phase year 2023 and the magnitude of change compared to the 2023 baseline concentration. .... 21

Table 5.16: NO<sub>2</sub> Concentration during operation of the proposed development during the 2028 average day and the magnitude of change compared to the 2028 baseline concentration. .... 23

Table 5.17: PM<sub>10</sub> Concentration during operation of the proposed development during the 2028 average day and the magnitude of change compared to the 2028 baseline concentration. .... 23

Table 5.18: PM<sub>2.5</sub> Concentration during operation of the proposed development during the 2028 average day and the magnitude of change compared to the 2028 baseline concentration. .... 24

Table 5.19: NO<sub>2</sub> Concentration during operation of the proposed development during the 2028 busiest day and the magnitude of change compared to the 2028 baseline concentration. .... 24

Table 5.20: PM<sub>10</sub> Concentration during operation of the proposed development during the 2028 busiest day and the magnitude of change compared to the 2028 baseline concentration. .... 25

Table 5.21: PM<sub>2.5</sub> concentration during operation of the proposed development during the 2028 busiest day and the magnitude of change compared to the 2028 baseline concentration. .... 25

Table 5.22: Summary of effects for the construction phase..... 28

Table 5.23: Summary of effects for both typical and busiest day operational phase. .... 28

Table 5.24: Summary of effects for the removal and reinstatement phase..... 28

## Figures

Figure 5.1: Northern Park and Ride site boundary and representative receptors.

## Plates

**None provided.**

## Appendices

Appendix 5A: Dust Risk Assessment for Northern Park and Ride and Darsham.

## 5. Air Quality

### 5.1 Introduction

5.1.1 This chapter of **Volume 3** of the **Environmental Statement (ES)** presents an assessment of the air quality effects arising from the construction, operation and removal and reinstatement of the northern park and ride at Darsham (referred to throughout this volume as the ‘proposed development’). This includes an assessment of potential impacts, the significance of effects, the requirements for mitigation and the residual effects.

5.1.2 Detailed descriptions of the northern park and ride site (referred to throughout this volume as the ‘site’), the proposed development and the different phases of development are provided in **Chapters 1** and **2** of this volume of the **ES**. A glossary of terms and list of abbreviations used in this chapter is provided in **Volume 1, Appendix 1A** of the **ES**.

5.1.3 This assessment has been informed by the **Transport Assessment** (Doc Ref. 8.5), in particular the road traffic data which has been modelled to assess the potential impacts from road traffic emissions in the vicinity of the proposed development.

5.1.4 This assessment has also been informed by data presented in the following technical appendices:

- **Volume 2, Appendix 12B** of the **ES**: Transport Emissions Assessment; and
- **Appendix 5A** of this volume of the **ES**: Dust Risk Assessment for Northern Park and Ride at Darsham.

### 5.2 Legislation, policy, and guidance

5.2.1 **Volume 1, Appendix 6H** of the **ES** identifies and describes legislation, policy and guidance of relevance to the assessment of the potential air quality impacts associated with the Sizewell C Project across all **ES** volumes.

5.2.2 This section provides an overview of the specific legislation, policy and guidance of relevance to the proposed development.

#### a) International

5.2.3 International legislation relating to the air quality assessment include:

- European Ambient Air Quality Directive 2008 (2008/50/EC) (Ref. 5.1); and
  - Fourth Air Quality Daughter Directive 2004 (2004/107/EC) (Ref. 5.2).
- 5.2.4 The requirements of these, as relevant to the air quality assessment, are set out in **Volume 1, Appendix 6H** of the **ES**.
- b) **National**
- 5.2.5 National legislation and policies relating to the air quality assessment include:
- Air Quality Standards Regulations 2010 (Ref. 5.3); and
  - National Air Quality Strategy (Ref. 5.4).
- 5.2.6 The requirements of these, as relevant to the air quality assessment, are set out in **Volume 1, Appendix 6H** of the **ES**.
- 5.2.7 The Overarching National Policy Statement for Energy (NPS EN-1) (Ref. 5.5), and the National Policy Statement for Nuclear Power Generation (NPS EN-6) (Ref. 5.6) set out requirements for air quality associated with the development of major energy infrastructure. These requirements are discussed in detail in **Volume 1, Appendix 6H** of the **ES**.
- c) **Regional**
- 5.2.8 Regional policy relating to the air quality assessment includes the Suffolk Local Transport Plan Parts 1 and 2 (Ref. 5.7).
- 5.2.9 The requirements of this, as relevant to the air quality assessment, are set out in **Volume 1, Appendix 6H** of the **ES**.
- d) **Local**
- 5.2.10 Local policy relating to the air quality assessment include:
- Suffolk Coastal District Council (SCDC) Core Strategy and Development Management Policies (Ref. 5.8); and
  - SCDC Final Draft Local Plan (Ref. 5.9).
- 5.2.11 The requirements of these, as relevant to the air quality assessment, are set out in **Volume 1, Appendix 6H** of the **ES**.

#### e) Guidance

5.2.12 Guidance relating to the air quality assessment include:

- Highways England's Sustainability & Environment Appraisal LA 105 Air quality (Ref. 5.10);
- Institute of Air Quality Management (IAQM) and Environmental Protection UK, Land-Use Planning & Development Control: Planning for Air Quality (Ref. 5.11);
- IAQM's Guidance on the assessment of dust from demolition and construction (Ref. 5.12);
- IAQM's A guide to the assessment of air quality impacts on designated nature conservation sites (Ref. 5.13); and
- National Atmospheric Emissions Inventory emission factors (Ref. 5.14).

5.2.13 Further details of these, as relevant to the air quality assessment, are set out in **Volume 1, Appendix 6H** of the **ES**.

### 5.3 Methodology

#### a) Scope of the assessment

5.3.1 The generic Environmental Impact Assessment (EIA) methodology is detailed in **Volume 1, Chapter 6** of the **ES**.

5.3.2 The full method of assessment for air quality that has been applied for the Sizewell C Project is detailed in **Volume 1, Appendix 6H** of the **ES**.

5.3.3 This section provides specific details of the air quality methodology applied to the assessment of the proposed development, and a summary of the general approach to provide appropriate context for the assessment that follows. The scope of assessment considers the impacts of the construction, operation, and removal and reinstatement of the proposed development, and consideration has been given to air quality effects arising from construction dust (arising from construction activities and non-road mobile machinery (NRMM) during both the construction and removal and reinstatement phases) and road traffic emissions (for all phases).

5.3.4 The scope of the assessment has been established through a formal EIA scoping process undertaken with the Planning Inspectorate (PINS). A request for an EIA scoping opinion was initially issued to the PINS in 2014,

with an updated request issued in 2019, see **Volume 1, Appendix 6A** of the **ES**.

5.3.5 Comments raised in the EIA scoping opinion received in 2014 and 2019 have been taken into account in the development of the assessment methodology. These are detailed in **Volume 1, Appendices 6A to 6C** of the **ES**. Project-wide comments but no site-specific comments were raised.

b) Consultation

5.3.6 The scope of the assessment has also been informed by ongoing consultation and engagement with statutory consultees throughout the design and assessment process. Consultation on the assessment methodology and conclusions for the main development site and associated developments, including the northern park and ride, has been undertaken with Suffolk County Council and East Suffolk Council. A summary of consultation relating to the air quality assessment is provided in **Volume 1, Appendix 6H** of the **ES**.

c) Study area

5.3.7 The geographical extent of the study area, determined using the methodology set out in **Volume 1, Appendix 6H** of the **ES**, for dust emissions includes:

- the site; and
- the area within 350 metres (m) from the site boundary, and 350m from public roads up to 500m from the site entrance.

5.3.8 The study area for road traffic emissions is an area 500m from the site entrance which includes the A12 and the proposed access route to the park and ride facility. The changes to air pollutant concentrations on the wider transport network are considered in **Volume 2, Appendix 12B: Transport Emissions Assessment** of the **ES**.

5.3.9 The combined study area and the location of representative receptors considered within this assessment are illustrated on **Figure 5.1** of this volume. Receptors YX10, YX11 and YX12 are marked twice on the figure as the nearest point of a sensitive receptor to road traffic emissions (for example 'YX10'), and the nearest point at the same property to the source of construction dust emissions (for example 'YX10c') are different.

#### d) Assessment scenarios

5.3.10 The assessment scenarios for the proposed development comprise the construction phase, operational phase, and the removal and reinstatement phase of the site. The assessment scenarios are as follows:

- Construction: consideration of ambient air quality and dust impacts during the construction of the proposed development during the early years of construction of the Sizewell C Project (2023). The construction programme is likely to take place over a number of phases over a total duration of up to 18 months. The assessment is divided into on-site emissions from construction activities and off-site emissions from road traffic movements.
- Operation: the proposed development would only be operational during the construction phase of the Sizewell C main development site. The assessment considers the emissions from road traffic using the proposed development during the peak construction year of the Sizewell C Project (2028). The assessment for the operational phase of the proposed development considers off-site emissions from road traffic movements.
- Removal and reinstatement: consideration of ambient air quality and dust impacts during the removal of the proposed development, and the reinstatement of the site to agricultural use. The assessment considers on-site emissions from demolition activities and off-site emissions from road traffic movements.

5.3.11 The traffic composition and flow data come from the **Transport Assessment** (Doc Ref. 8.5) for the baseline, construction (2023) and operation (2028) scenarios. This information is inherently cumulative as it includes traffic flows associated with consented developments. Separate modelling for the removal and reinstatement has not been completed. However, the number of additional traffic movements associated with the removal and reinstatement of the site is not anticipated to be greater than the construction phase (2023) therefore a qualitative assessment is presented on this basis.

#### e) Assessment criteria

5.3.12 As described in **Volume 1, Chapter 6** of the **ES**, the EIA methodology considers whether impacts of the proposed development would have an effect on any resources or receptors.

5.3.13 A detailed description of the assessment methodology used to assess the potential effects on the air quality arising from the proposed development is



provided in **Volume 1, Appendix 6H** of the **ES**. A summary of the assessment criteria used in this assessment is presented in the following sub-sections.

i. **Construction dust**

**5.3.14** The assessment of construction dust effects (also considered in the removal and reinstatement phase) is determined by considering the magnitude of impacts and sensitivity of receptors that could be affected in order to classify effects.

**5.3.15** The significance of effects for construction phase dust emissions (including use of NRMM) are determined using professional judgement based on the risk of dust impacts, and the appropriateness of mitigation to control emissions of dust and exhaust emissions from NRMM identified within the **Code of Construction Practice (CoCP)** (Doc Ref. 8.11).

**5.3.16** A detailed description of the assessment methodology used to assess the potential effects on air quality arising from construction dust, and exhaust emissions from NRMM is provided in **Volume 1, Appendix 6H** of the **ES**. A summary of the criteria used in this assessment is presented in the following sub-sections.

**Sensitivity**

**5.3.17** The assessment of assigning the levels of sensitivity to receptors is set out in **Table 5.1**.

**Table 5.1: Assessment of the value or sensitivity of receptors for air quality.**

Sensitivity	Human Perception of Dust Soiling Effects.	Particulate Matter (PM <sub>10</sub> ) Health Effects.	Ecological Dust Deposition Effects.
High	Experience a high level of amenity; appearance, aesthetics or value of property would be diminished by dust soiling; and receptor expected to be present continuously or regularly for example residential, museums, car showrooms or commercial horticulture.	Public present for eight hours per day or more, for example residential, schools, care homes.	International/national designation and the designated feature is sensitive to dust soiling effects, for example Special Areas of Conservation for acid heathlands, or lichens, vascular species on Red Data List (Joint Nature Conservation Committee).
Medium	Enjoy a reasonable level of amenity; appearance, aesthetics or value of property could be	Only workforce present (no residential or high sensitivity receptors) eight hours per day or more.	Important plant species – unknown sensitivity to dust soiling; national designation which may be

Sensitivity	Human Perception of Dust Soiling Effects.	Particulate Matter (PM <sub>10</sub> ) Health Effects.	Ecological Dust Deposition Effects.
	diminished by soiling; receptor not expected to be present continuously, or regularly for example parks or places of work.		sensitive, for example Site of Special Scientific Interest with dust sensitive feature.
Low	Enjoyment of amenity not reasonably expected; appearance, aesthetics or value of property not diminished by soiling; receptors are transient or present for a limited period of time; for example, playing fields, farmland, footpaths, short-term car parks* and roads.	Transient human exposure, for example footpaths, playing fields, parks.	Local designation where feature may be sensitive to dust soiling, for example local nature reserve.

\*subject to typical usage, could be high sensitivity depending on the duration and frequency that cars would be expected to be parked there, and the level of amenity expected.

### Magnitude

- 5.3.18 The magnitude of risk to air quality from construction dust is based on the IAQM (Ref. 5.12) suggested criteria.
- 5.3.19 The descriptors used to classify the potential magnitude of emissions from construction and removal and reinstatement activities are the first step in establishing the risks to air quality using the classification shown in **Table 5.2**.

**Table 5.2: Dust emission magnitude classification.**

Magnitude	Demolition	Earthworks	Construction	Trackout
High	Total building volume greater than 50,000m <sup>3</sup> , potentially dusty construction material (for example concrete) on-site crushing and screening, demolition	Site area greater than 1 hectare (ha), potentially dusty soil type (for example clay), greater than ten heavy earth moving vehicles at once, bunds greater than 8m	Total building volume greater than 100,000m <sup>3</sup> , on-site concrete batching, sandblasting.	Greater than 50 heavy duty vehicles (HDV) <sup>1</sup> (greater than 3.5 tonnes) peak outward movements per day, potentially dusty surface material (for

<sup>1</sup> The term heavy duty vehicles (HDV) is used as an extension of heavy good vehicles (HGVs) to include consideration of other heavy vehicles, for examples buses and/or coaches.

Magnitude	Demolition	Earthworks	Construction	Trackout
	activities greater than 20m above ground.	high, total material moved greater than 100,000 tonnes.		example high clay content), unpaved road length greater than 100m.
Medium	Total building volume 20,000–50,000m <sup>3</sup> , potentially dusty construction material, demolition activities 10–20m above ground.	Site area 0.25–1ha, moderately dusty soil type (for example silt), five to ten heavy earth moving vehicles at once, bunds 4–8m high, total material moved 20,000–100,000 tonnes.	Total building volume 25,000–100,000m <sup>3</sup> , potentially dusty materials for example concrete, on-site concrete batching.	10–50 HDV (greater than 3.5 tonnes) peak outward movements per day, moderately dusty surface material (for example high clay content), unpaved road length 50–100m.
Low	Total building volume less than 20,000m <sup>3</sup> , construction material with low potential for dust (for example metal/timber), demolition activities less than 10m above ground, demolition during wetter months.	Site area less than 0.25, large grain soil type (for example sand), less than five heavy earth moving vehicles at once, bunds less than 4m high, total material moved less than 20,000 tonnes.	Total building volume less than 25,000m <sup>3</sup> , low dust potential construction materials for example metal/timber.	Less than ten HDV (greater than 3.5 tonnes) peak outward movements per day, surface material low dust potential, unpaved road length less than 50m.

Effect definitions

5.3.20 The risk definitions for dust emissions during different activities are shown in **Table 5.3** to **Table 5.5**.

**Table 5.3: Risk of dust impacts – demolition.**

Sensitivity of Area.	Potential Dust Emission Magnitude without Mitigation.		
	Large	Medium	Small
High	High risk.	Medium risk.	Medium risk.
Medium	High risk.	Medium risk.	Low risk.
Low	Medium risk.	Low risk.	Negligible risk.

**Table 5.4: Risk of dust impacts – earthworks and construction.**

Sensitivity of Area.	Potential Dust Emission Magnitude without Mitigation.		
	Large	Medium	Small
High	High risk.	Medium risk.	Low risk.
Medium	Medium risk.	Medium risk.	Low risk.
Low	Low risk.	Low risk.	Negligible risk.

**Table 5.5: Risk of dust impacts – trackout.**

Sensitivity of Area.	Potential Dust Emission Magnitude without Mitigation.		
	Large	Medium	Small
High	High risk.	Medium risk.	Low risk.
Medium	Medium risk.	Low risk.	Negligible risk.
Low	Low risk.	Low risk.	Negligible risk.

5.3.21 Based on the risk level of dust impacts, suitable mitigation should be applied to reduce the potential effects from dust emissions. The significance of dust effects is determined based on the mitigation proposed.

ii. Transport emissions

5.3.22 A detailed description of the assessment methodology used to assess the potential effects on air quality arising from the proposed development is provided in **Volume 1, Appendix 6H** of the **ES**. A summary of the assessment descriptors used in the Transport Emissions Assessment, provided in **Volume 2, Appendix 12B** of the **ES**, is presented in the following sub-sections.

Magnitude

5.3.23 The magnitude of impact from transport emissions is based on the IAQM (Ref. 5.11) suggested descriptors.

5.3.24 The descriptors for the assessment of magnitude are shown in **Table 5.6**.

**Table 5.6: Assessment of transport emission magnitude of impact on air quality.**

Magnitude of Change Descriptor.	Substance	Annual Concentration (µg/m³).	Mean	Justification
High	Nitrogen Dioxide (NO <sub>2</sub> ) and PM <sub>10</sub> .	Increase/decrease greater than 4.		Change in concentration relative to air quality objective value of greater than 10%.
	PM <sub>2.5</sub> .	Increase/decrease greater than 2.5.		
Medium	NO <sub>2</sub> and PM <sub>10</sub> .	Increase/decrease 2–4.		Change in concentration relative to air quality objective value of between 6% and 10%.
	PM <sub>2.5</sub> .	Increase/decrease 1.4–2.5.		
Low	NO <sub>2</sub> and PM <sub>10</sub> .	Increase/decrease 0.8–1.9.		Change in concentration relative to air quality objective value of between 2% and 5%.
	PM <sub>2.5</sub> .	Increase/decrease 0.5–1.3.		
Very low.	NO <sub>2</sub> and PM <sub>10</sub> .	Increase/decrease 0.4–0.7.		Change in concentration relative to air quality objective value of 1%.
	PM <sub>2.5</sub> .	Increase/decrease 0.3–0.4.		
Imperceptible	NO <sub>2</sub> and PM <sub>10</sub> .	Increase/decrease less than 0.4.		Change in concentration relative to air quality objective value of less than 1%.
	PM <sub>2.5</sub> .	Increase/decrease less than 0.3.		

Effect definition

5.3.25 The definitions of effect of road traffic emissions for air quality are shown in **Table 5.7** and **Table 5.8**.

**Table 5.7: Effect descriptors for annual mean NO<sub>2</sub> and PM<sub>10</sub>.**

Annual Pollutant Concentration at Receptor Assessment Year (µg/m <sup>3</sup> ).	Mean at in Year	Magnitude of Impact.				
		Imperceptible	Very low.	Low	Medium	High
Less than or equal to 30.2		Negligible	Negligible	Negligible	Minor	Moderate
Greater than 30.2 to 37.8		Negligible	Negligible	Minor	Moderate	Moderate
Greater than 37.8 to 41.1		Negligible	Minor	Moderate	Moderate	Major
Greater than 41.1 to less than 43.8		Negligible	Moderate	Moderate	Major	Major
Greater than or equal to 43.8		Negligible	Moderate	Major	Major	Major

**Table 5.8: Effect descriptors for annual mean PM<sub>2.5</sub>.**

Annual Pollutant Concentration at Receptor Assessment Year (µg/m <sup>3</sup> ).	Mean at in Year	Magnitude of Impact.				
		Imperceptible	Very low.	Low	Medium	High
Less than or equal to 18.9		Negligible	Negligible	Negligible	Minor	Moderate
Greater than 18.9 to 23.6		Negligible	Negligible	Minor	Moderate	Moderate
Greater than 23.6 to 25.6		Negligible	Minor	Moderate	Moderate	Major
Greater than 25.6 to less than 27.4		Negligible	Moderate	Moderate	Major	Major
Greater than or equal to 27.4		Negligible	Moderate	Major	Major	Major

5.3.26 Following the classification of an effect as presented in **Table 5.7** and **Table 5.8**, a clear statement is made as to whether the effect is 'significant' or 'not significant'. As a general rule, major and moderate effects are considered to be significant, and minor and negligible effects are considered to be not significant. However, professional judgement is also applied where appropriate. Where there is an increase in pollutant concentration resulting from the proposed development, the effect is adverse. Where there is a decrease in pollutant concentration, the effect is beneficial.

f) **Assessment methodology**

5.3.27 The methodology for the assessment of changes in air pollutant concentrations is set out in detail within **Volume 1, Appendix 6H** of the **ES**. The general approach is described in the following sections.

5.3.28 The change in air quality conditions are considered at receptors that are representative of changes that would occur at other sensitive receptors located nearby. The representative receptors, provided in **Figure 5.1**, are those located closest to the site boundary and the affected road network within the study area.

5.3.29 The magnitude of change in air pollutant concentrations of construction dust deposition rates would be greatest at these representative locations. Assessment of the representative receptors therefore represents a worst-case assessment of the potential construction dust effects. The sensitivity of individual representative receptors to construction dust is set out in **Appendix 5A** of this volume of the **ES**.

5.3.30 All receptors are considered to be of equal sensitivity to transport emissions as any member of the public could be present, including more sensitive members such as the young, elderly or unwell. Assessment of the representative receptors therefore represents a worst-case assessment of the potential transport emission effects.

i. **Construction dust**

5.3.31 The assessment of likely changes in emissions of coarse particulate matter (PM<sub>10</sub> and dust) has been considered at the nearest representative receptor in all directions from the site boundary. Coarse particulate matter has been assessed as this can have adverse effects on human health, amenity and ecology where levels exceed their objective values, as set out in **Volume 1, Appendix 6H** of the **ES**.

5.3.32 There is a risk of proposed construction activities, demolition and earthworks including vegetation and site clearance and stockpiling of soils,

construction works (including construction of new road, signage and landscaping) and potential track-out of dusty materials onto public roads from HDV movements on unpaved surfaces and mud transferred onto the highway, up to 500m from site exit giving rise to perceptible changes in dust deposition rates and to changes in concentrations of PM<sub>10</sub> in air. Taking into account the sensitivity of receptors to these changes, the effectiveness of tertiary mitigation measures, as set out in the **CoCP** (Doc Ref. 8.11), are considered based on the professional judgement of a suitably qualified and experienced person. Where the risk of a significant effect is identified, additional site-specific mitigation measures are proposed so that there are no likely significant residual effects.

## ii. Transport emissions

- 5.3.33** The Transport Emissions Assessment, provided in **Volume 2, Appendix 12B** of the **ES**, details the technical dispersion modelling method and predicted air pollutant concentrations resulting from HDVs, light duty vehicles, and rail traffic for all scenarios of the Sizewell C Project on the wider transport network. NO<sub>2</sub>, PM<sub>10</sub> and PM<sub>2.5</sub> are assessed as these can cause adverse effects to human health and ecology at levels exceeding their objective values.
- 5.3.34** The traffic model includes data for all associated developments and the Sizewell C main development site, therefore the study area for the Transport Emissions Assessment, provided in **Volume 2, Appendix 12B** of the **ES**, extends from Lowestoft to Ipswich for the Sizewell C Project. However, for the purpose of this assessment, the only road within the study area likely to be affected by the proposed development is the A12 adjacent to the site. This was modelled within the Transport Emissions Assessment as provided in **Volume 2, Appendix 12B** of the **ES**. Traffic emissions are assessed for the representative year for early construction of the Sizewell C Project (2023) and for the anticipated peak construction of the Sizewell C Project (2028).
- 5.3.35** Construction of the proposed development is not anticipated to generate as much traffic as either the early construction year (2023) or the peak construction year of the Sizewell C Project (2028).
- 5.3.36** The assessment of potential impacts presented in this chapter consider the future baseline and with development scenarios for 2023 and 2028. The future baselines for the representative years 2023 and 2028, informed by projected traffic data for these years, are used for comparison with the future construction and operation scenarios to assess how the proposed development is expected to have an effect on air quality.



5.3.37 Traffic data for the construction year (2023) of the proposed development is based on traffic flow for an average day during the ‘early year’ construction scenario for the Sizewell C Project. This includes construction workers and HDVs travelling to and from the main development site, the proposed development site and other Sizewell C Project sites.

5.3.38 Traffic data for the operational phase year, during the peak construction of the Sizewell C Project (2028), is based on two scenarios, an average day and a busy day. These include traffic using the proposed development and other associated developments, and construction traffic for the Sizewell C main development site. Busy day traffic data includes additional traffic expected in the event there is an outage at the Sizewell B power station.

g) Assumptions and limitations

5.3.39 Assumptions and limitations relevant to this assessment, for example emission rates and engine specifications, are described in **Volume 1, Appendix 6H** of the **ES**. There are no site-specific assumptions or limitations.

## 5.4 Baseline environment

5.4.1 This section presents a description of the baseline environmental characteristics within the site and in the surrounding area.

a) Current baseline

5.4.2 The closest human receptors to the site are located along the A12 (YX1, YX10 to YX13, YX15 and YX16), Willow Marsh Lane (YX14), and The Street (YX17) as identified in **Figure 5.1**.

5.4.3 Sillett’s Wood county wildlife site (CWS) lies approximately 300m north of the proposed development. However, due to the distance of the Sillett’s Wood CWS from the site and affected road network, the CWS is screened out and is not included in the construction or operational phase air quality assessment for the proposed development.

5.4.4 There are no air quality management areas within the study area.

5.4.5 NO<sub>2</sub> and particulate matter (PM<sub>10</sub> and PM<sub>2.5</sub>) 2018 background concentrations within the site are projected to be between 8.0 and 8.4µg/m<sup>3</sup> for NO<sub>2</sub>, between 15.2 and 15.9µg/m<sup>3</sup> for PM<sub>10</sub> and between 9.1 and 9.3µg/m<sup>3</sup> for PM<sub>2.5</sub> (Ref. 5.15).

5.4.6 The overall predicted baseline concentrations, including nearby road traffic contributions, for pollutants NO<sub>2</sub>, PM<sub>10</sub> and PM<sub>2.5</sub> at sensitive receptors near

the site are reported in **Table 5.9** to one decimal place. Further details on modelled 2018 baseline pollutant concentrations at receptors can be found in **Volume 2, Appendix 12B** of the **ES**.

**Table 5.9: NO<sub>2</sub>, PM<sub>10</sub> and PM<sub>2.5</sub> Concentrations for the Baseline Year 2018 at nearby Sensitive Receptors.**

Receptor	2018 concentration. (µg/m <sup>3</sup> )	NO <sub>2</sub>	2018 concentration. (µg/m <sup>3</sup> )	PM <sub>10</sub>	2018 concentration. (µg/m <sup>3</sup> )	PM <sub>2.5</sub>
YX1	19.3		17.0		11.0	
YX10	14.9		16.4		10.2	
YX11	10.1		15.9		9.5	
YX12	9.7		15.9		9.5	
YX13	15.3		16.6		10.4	
YX14	8.2		15.8		9.3	
YX15	12.8		15.6		9.8	
YX16	13.0		16.4		10.0	
YX17	8.6		15.2		9.2	

\* All values have been rounded to the nearest decimal place.

**5.4.7** Dust levels are related to the action of wind on exposed soils and arable fields in the area, long range transport of airborne particulate matter, and climatic conditions year to year, but existing dust levels are likely to be low given the arable nature of the existing land use.

**b) Future baseline**

**5.4.8** No notable changes are expected in land use in the surrounding area, and it is expected that the future baseline rates of dust deposition are likely to be similar to current levels.

**5.4.9** NO<sub>2</sub> and particulate matter (PM<sub>10</sub> and PM<sub>2.5</sub>) 2023 background concentrations within the site are projected to be between 6.7 and 6.9µg/m<sup>3</sup> for NO<sub>2</sub>, between 14.3 and 15.1µg/m<sup>3</sup> for PM<sub>10</sub> and between 8.4 and 8.6µg/m<sup>3</sup> for PM<sub>2.5</sub>, a reduction in all three pollutants (Ref. 5.15).

**5.4.10** NO<sub>2</sub> and particulate matter 2028 background concentrations within the site are projected to be between 6.0 and 6.2µg/m<sup>3</sup> for NO<sub>2</sub>, between 14.0 to 14.8µg/m<sup>3</sup> for PM<sub>10</sub> and between 8.2 and 8.3µg/m<sup>3</sup> for PM<sub>2.5</sub>, an overall reduction in all three pollutants (Ref. 5.15).

5.4.11 The effects resulting from the proposed development at potential future receptors from committed developments in the study area are represented by effects at receptors already included in the assessment. For example, air quality effects at the proposed hotel (application reference DC/14/0420/OUT) are represented by receptor YX13. Therefore, no additional receptors need to be included for the future scenarios. In addition, the traffic composition and flow data come from the **Transport Assessment** (Doc Ref. 8.5) for the baseline, construction and operation scenarios. This information is inherently cumulative as it includes traffic flows associated with consented developments.

5.4.12 The future baseline pollutant concentrations at nearby sensitive receptors for the years 2023 and 2028 are presented in **Table 5.10** and **Table 5.11**, respectively, reported to one decimal place. Further details of modelled pollutant concentrations for the years 2023 and 2028 can be found in **Volume 2, Appendix 12B** of the **ES**.

**Table 5.10: NO<sub>2</sub>, PM<sub>10</sub> and PM<sub>2.5</sub> concentrations for the baseline year 2023 at nearby sensitive receptors.**

Receptor	2023 concentration. (µg/m <sup>3</sup> )	NO <sub>2</sub>	2023 concentration. (µg/m <sup>3</sup> )	PM <sub>10</sub>	2023 concentration. (µg/m <sup>3</sup> )	PM <sub>2.5</sub>
YX1	14.5		16.1		10.2	
YX10	11.4		15.5		9.5	
YX11	8.1		15.1		8.8	
YX12	7.9		15.1		8.8	
YX13	11.7		15.7		9.6	
YX14	6.8		14.9		8.6	
YX15	9.9		14.7		9.1	
YX16	10.1		15.5		9.3	
YX17	7.1		14.4		8.5	

\* All values have been rounded to the nearest decimal place.

**Table 5.11: NO<sub>2</sub>, PM<sub>10</sub> and PM<sub>2.5</sub> concentrations for the baseline year 2028 at nearby sensitive receptors.**

Receptor	2028 concentration. (µg/m <sup>3</sup> )	NO <sub>2</sub>	2028 concentration. (µg/m <sup>3</sup> )	PM <sub>10</sub>	2028 concentration. (µg/m <sup>3</sup> )	PM <sub>2.5</sub>
YX1	11.4		15.8		10.0	
YX10	9.2		15.2		9.3	

Receptor	2028 concentration. (µg/m <sup>3</sup> )	NO <sub>2</sub>	2028 concentration. (µg/m <sup>3</sup> )	PM <sub>10</sub>	2028 concentration. (µg/m <sup>3</sup> )	PM <sub>2.5</sub>
YX11	6.9		14.8		8.6	
YX12	6.8		14.7		8.5	
YX13	9.4		15.4		9.4	
YX14	6.1		14.6		8.3	
YX15	8.2		14.4		8.8	
YX16	8.3		15.2		9.1	
YX17	6.3		14.1		8.3	

\* All values have been rounded to the nearest decimal place.

## 5.5 Environmental design and mitigation

5.5.1 As detailed in **Volume 1, Chapter 6** of the **ES**, a number of primary and tertiary mitigation measures have been identified through the iterative EIA process, and have been incorporated into the design and construction planning of the proposed development. Tertiary mitigation measures are legal requirements or are standard practices that would be implemented as part of the proposed development.

5.5.2 The assessment of likely significant effects of the proposed development assumes that primary and tertiary mitigation measures are in place. For air quality, these measures are identified in the following sections, with a summary provided on how the measures contribute to the mitigation, and management of potentially significant environmental effects.

### a) Primary mitigation

5.5.3 Primary mitigation is often referred to as ‘embedded mitigation’ and includes modifications to the location or design to mitigate impacts; these measures become an inherent part of the proposed development.

5.5.4 Primary mitigation for the proposed development includes:

- site selection to minimise distance of park and ride facility from A12;
- site access would be located at least 10m, from residential receptors; and
- re-use of soils on-site to form bunds instead of transporting them for off-site storage.

5.5.5 Primary measures to minimise and manage additional traffic on the roads associated with the construction and operation of the Sizewell C Project are set out in **Volume 2, Chapter 10** of the **ES**.

b) **Tertiary mitigation**

5.5.6 Tertiary mitigation will be required regardless of any EIA assessment, as it is imposed, for example, as a result of legislative requirements and/or standard sectoral practices.

5.5.7 Air quality impacts arising from the construction and removal and reinstatement phases would be managed through a range of control measures detailed in the **CoCP** (Doc Ref. 8.11), which will include measures as per the IAQM Guidance (Ref. 5.12) based on a ‘high risk’ site. These measures will be incorporated into construction working practices to reduce the likelihood of significant adverse dust impacts, and would include measures such as the requirement to:

- avoid direct site run-off of water or mud;
- use of surface covering (seeding of earthworks, hardstanding surface for car park) to minimise extent of exposed soils and minimise potential resuspension of dust and to prevent wind whipping;
- covering potentially dusty loads (loose earth, spoil, aggregates etc) in transit;
- ensure an adequate water supply on the site for effective dust/particulate matter suppression/mitigation, using non-potable water where possible and appropriate;
- display the name and contact details of person(s) accountable for air quality and dust issues on the site boundary; and
- develop and implement dust management measures, in accordance with the **CoCP** (Doc Ref. 8.11).

5.5.8 The contractors will prepare Construction Environmental Management Plans including dust management measures, in accordance with the **CoCP** (Doc Ref. 8.11). An **Outline Dust Management Plan** is also included in **Volume 2, Appendix 12A**.

5.5.9 During construction, a **Construction Traffic Management Plan** (Doc Ref. 8.7) and a **Construction Workforce Travel Plan** (Doc Ref. 8.8) would be implemented to reduce and manage the effects of traffic generated by the Sizewell C Project (see **Volume 2, Chapter 10** of the **ES**).

5.5.10 Mitigation measures applied during the construction phase will also be applied during the removal and reinstatement works as construction dust impacts are likely to be similar.

## 5.6 Assessment

### a) Introduction

5.6.1 This section presents the findings of the air quality assessment for the construction, operational and removal and reinstatement phases of the proposed development.

5.6.2 This section identifies any likely significant effects that are predicted to occur and **section 5.7** of this chapter then highlights any secondary mitigation and monitoring measures that are proposed to minimise any adverse significant effects (if required).

### b) Construction

5.6.3 The potential impacts on sensitive receptors associated with the construction of the proposed development include fugitive emissions of dust, emissions from NRMM on the site, emissions from HDVs accessing the site, and emissions from vehicles carrying workers to and from the site.

#### i. Construction dust

5.6.4 A dust risk assessment has been undertaken for the proposed development, which also considers the risk from NRMM used to undertake works. A summary of the assessment is presented in **Table 5.12**, and full details of the assessment are provided in **Appendix 5A** of this volume of the **ES**.

**Table 5.12: Potential risk of dust impacts from activities without applied mitigation.**

Potential impact.	Risk			
	Earthworks: large magnitude.	Construction: medium magnitude.	Trackout: medium magnitude.	Demolition: medium magnitude.
Dust Soiling	High risk.	Medium risk.	Medium risk.	Medium risk.
Human Health	Medium risk.	Medium risk.	Low risk.	Medium risk..
Ecological	Screened out.			

5.6.5 All residential receptors are considered to be high sensitivity receptors to health and dust soiling effects. The principal risk is anticipated to be related to earthworks, as this phase of construction can typically require a high volume of material to be moved. A high level of activity can potentially place the dust emissions category as ‘large’ by IAQM classification (Ref. 5.12), with the likelihood of ‘high’ risk based on the number and sensitivity of local receptors. Each risk category has the potential to lead to proportional adverse, albeit temporary impacts which have the potential to be significant without appropriate mitigation.

5.6.6 However, assuming all primary and tertiary mitigation measures (as detailed in section 5.5) are effectively implemented and monitored through the **CoCP** (Doc Ref. 8.11), at the level recommended by the dust risk assessment, any construction dust effects would likely be negligible, and would therefore be **not significant** for any of the proposed construction activities at the site.

ii. Construction traffic

5.6.7 It is expected that the number of HDV movements required to construct the proposed development would not exceed the IAQM screening threshold (Ref. 5.11) of more than 100 Annual Average Daily Traffic required for a detailed dispersion modelling assessment. However, due to the number of developments undergoing construction during the early years construction phase of the Sizewell C Project (2023) in the wider study area (Lowestoft to Ipswich), a detailed assessment of transport emissions for the construction phase scenario has been undertaken.

5.6.8 The predicted concentrations for NO<sub>2</sub>, PM<sub>10</sub> and PM<sub>2.5</sub> resulting from traffic emissions in the area of the proposed development during construction, based on the average day during the early years (2023), and the magnitude of change from the predicted baseline conditions are shown in **Table 5.13** to **Table 5.15** reported to one decimal place. Further details on modelled pollutant concentrations for the year 2023 can be found in **Volume 2, Appendix 12B** of the **ES**.

**Table 5.13: NO<sub>2</sub> Concentration for construction phase year 2023 and the magnitude of change compared to the 2023 baseline concentration.**

Receptor	2023 average day*.		Magnitude of change descriptor.	Effect descriptor.
	Concentration (µg/m <sup>3</sup> )	Magnitude of change (µg/m <sup>3</sup> ).		
YX1	14.8	0.3	Imperceptible	Negligible
YX10	11.5	0.1	Imperceptible	Negligible

Receptor	2023 average day*.		Magnitude of change descriptor.	Effect descriptor.
	Concentration (µg/m <sup>3</sup> )	Magnitude of change (µg/m <sup>3</sup> ).		
YX11	11.5	0.1	Imperceptible	Negligible
YX12	8.1	0.1	Imperceptible	Negligible
YX13	7.9	0.1	Imperceptible	Negligible
YX14	11.8	Less than 0.1.	Imperceptible	Negligible
YX15	10.0	0.1	Imperceptible	Negligible
YX16	10.2	0.2	Imperceptible	Negligible
YX17	7.1	Less than 0.1.	Imperceptible	Negligible

\* All values have been rounded to the nearest decimal place.

**Table 5.14: PM<sub>10</sub> Concentration for construction phase year 2023 and the magnitude of change compared to the 2023 baseline concentration.**

Receptor	2023 average day*.		Magnitude of change descriptor.	Effect descriptor.
	Concentration (µg/m <sup>3</sup> )	Magnitude of change (µg/m <sup>3</sup> ).		
YX1	16.8	0.7	Very Low.	Negligible
YX10	15.5	Less than 0.1.	Imperceptible	Negligible
YX11	15.1	Less than 0.1.	Imperceptible	Negligible
YX12	15.1	Less than 0.1.	Imperceptible	Negligible
YX13	15.7	Less than 0.1.	Imperceptible	Negligible
YX14	14.9	Less than 0.1.	Imperceptible	Negligible
YX15	14.8	Less than 0.1.	Imperceptible	Negligible
YX16	15.8	0.3	Imperceptible	Negligible
YX17	14.4	Less than 0.1.	Imperceptible	Negligible

\* All values have been rounded to the nearest decimal place.

**Table 5.15: PM<sub>2.5</sub> Concentration for construction phase year 2023 and the magnitude of change compared to the 2023 baseline concentration.**

Receptor	2023 average day*.		Magnitude of change descriptor.	Effect descriptor.
	Concentration (µg/m <sup>3</sup> )	Magnitude of change (µg/m <sup>3</sup> ).		
YX1	9.6	-0.6	Low	Negligible
YX10	9.5	Less than 0.1.	Imperceptible	Negligible



YX11	8.8	Less than 0.1.	Imperceptible	Negligible
YX12	8.8	Less than 0.1.	Imperceptible	Negligible
YX13	9.7	Less than 0.1.	Imperceptible	Negligible
YX14	8.6	Less than 0.1.	Imperceptible	Negligible
YX15	9.1	Less than 0.1.	Imperceptible	Negligible
YX16	9.1	0.2	Imperceptible	Negligible
YX17	8.5	Less than 0.1.	Imperceptible	Negligible

\* All values have been rounded to the nearest decimal place.

**5.6.9** Following the classification of effects of construction phase traffic, the effects of NO<sub>2</sub> and particulate matter (PM<sub>10</sub> and PM<sub>2.5</sub>) at nearby sensitive receptors are considered to be negligible. The overall effects on air quality resulting from traffic related to construction of the proposed development are **not significant**.

**iii. Inter-relationship effects**

**5.6.10** There are potential inter-relationship effects on ecological and amenity and recreation receptors as a result of changes to air quality during the construction phase of development. These potential impacts are considered within **Chapters 7 and 8** of this volume respectively. There is also the potential for impacts relating to soils management on site as detailed in **Chapter 10** of this volume, to give rise to air quality effects from dust. Inter-relationship effects on human health receptors are considered further in **Volume 2, Chapter 28**, and in **Volume 10, Chapter 2** respectively all found in the **ES**.

**c) Operation**

**i. Operation of the proposed development during the peak construction year of the Sizewell C Project (2028)**

**5.6.11** The air quality assessment for operation of the proposed development covers the peak year (2028) during the construction of the Sizewell C Project on its busiest days and on an average day.

**5.6.12** The predicted concentrations for NO<sub>2</sub>, PM<sub>10</sub> and PM<sub>2.5</sub> resulting from road traffic in the study area for the proposed development for the operational year 2028 average day scenarios, and the magnitude of change from the predicted baseline conditions, are shown in **Table 5.16, Table 5.17, and Table 5.18**, reported to one decimal place.

5.6.13 Further details on modelled air pollutant concentrations at receptors for the 2028 average day scenario can be found in **Volume 2, Appendix 12B** of the **ES**.

**Table 5.16: NO<sub>2</sub> Concentration during operation of the proposed development during the 2028 average day and the magnitude of change compared to the 2028 baseline concentration.**

Receptor	2028 average day*.		Change descriptor.	Effect descriptor.
	Concentration (µg/m <sup>3</sup> )	Magnitude of change (µg/m <sup>3</sup> ).		
YX1	12.3	0.9	Low	Negligible
YX10	9.7	0.5	Very Low.	Negligible
YX11	7.1	0.2	Imperceptible	Negligible
YX12	7.0	0.2	Imperceptible	Negligible
YX13	9.9	0.5	Very Low.	Negligible
YX14	6.1	Less than 0.1.	Imperceptible	Negligible
YX15	8.5	0.3	Imperceptible	Negligible
YX16	8.7	0.4	Very Low.	Negligible
YX17	6.3	0.1	Imperceptible	Negligible

\* All values have been rounded to the nearest decimal place.

**Table 5.17: PM<sub>10</sub> Concentration during operation of the proposed development during the 2028 average day and the magnitude of change compared to the 2028 baseline concentration.**

Receptor	2028 average day*.		Change descriptor.	Effect descriptor.
	Concentration (µg/m <sup>3</sup> )	Magnitude of change (µg/m <sup>3</sup> ).		
YX1	15.9	0.1	Imperceptible	Negligible
YX10	15.3	0.1	Imperceptible	Negligible
YX11	14.8	Less than 0.1.	Imperceptible	Negligible
YX12	14.8	Less than 0.1.	Imperceptible	Negligible
YX13	15.5	0.1	Imperceptible	Negligible
YX14	14.6	Less than 0.1.	Imperceptible	Negligible
YX15	14.5	0.1	Imperceptible	Negligible
YX16	15.3	0.1	Imperceptible	Negligible
YX17	14.1	Less than 0.1.	Imperceptible	Negligible

\* All values have been rounded to the nearest decimal place.

**Table 5.18: PM<sub>2.5</sub> Concentration during operation of the proposed development during the 2028 average day and the magnitude of change compared to the 2028 baseline concentration.**

Receptor	2028 average day*.		Change descriptor.	Effect descriptor.
	Concentration (µg/m <sup>3</sup> )	Magnitude of change (µg/m <sup>3</sup> ).		
YX1	10.2	0.2	Imperceptible	Negligible
YX10	9.4	0.1	Imperceptible	Negligible
YX11	8.6	0.1	Imperceptible	Negligible
YX12	8.6	0.1	Imperceptible	Negligible
YX13	9.5	0.1	Imperceptible	Negligible
YX14	8.3	Less than 0.1.	Imperceptible	Negligible
YX15	8.9	0.1	Imperceptible	Negligible
YX16	9.2	0.1	Imperceptible	Negligible
YX17	8.3	Less than 0.1.	Imperceptible	Negligible

\* All values have been rounded to the nearest decimal place.

**5.6.14** The predicted concentrations for NO<sub>2</sub>, PM<sub>10</sub> and PM<sub>2.5</sub> for the operational year 2028 busiest day scenario, and the magnitude of change from the predicted baseline conditions are shown in **Table 5.19**, **Table 5.20**, and **Table 5.21**, reported to one decimal place. Further details on modelled pollutant concentrations for the 2028 busiest day scenario can be found in **Volume 2, Appendix 12B** of the **ES**.

**Table 5.19: NO<sub>2</sub> Concentration during operation of the proposed development during the 2028 busiest day and the magnitude of change compared to the 2028 baseline concentration.**

Receptor	2028 busiest day*.		Change descriptor.	Effect descriptor.
	Concentration (µg/m <sup>3</sup> )	Magnitude of change (µg/m <sup>3</sup> )		
YX1	12.3	0.9	Low	Negligible
YX10	9.7	0.5	Very Low.	Negligible
YX11	7.1	0.2	Imperceptible	Negligible
YX12	7.0	0.2	Imperceptible	Negligible
YX13	9.9	0.5	Very Low.	Negligible
YX14	6.1	Less than 0.1.	Imperceptible	Negligible
YX15	8.5	0.3	Imperceptible	Negligible

Receptor	2028 busiest day*.		Change descriptor.	Effect descriptor.
	Concentration ( $\mu\text{g}/\text{m}^3$ )	Magnitude of change ( $\mu\text{g}/\text{m}^3$ )		
YX16	8.7	0.4	Very Low.	Negligible
YX17	6.3	0.1	Imperceptible	Negligible

\* All values have been rounded to the nearest decimal place.

**Table 5.20: PM<sub>10</sub> Concentration during operation of the proposed development during the 2028 busiest day and the magnitude of change compared to the 2028 baseline concentration.**

Receptor	2028 busiest day*.		Change descriptor.	Effect descriptor.
	Concentration ( $\mu\text{g}/\text{m}^3$ )	Magnitude of change ( $\mu\text{g}/\text{m}^3$ )		
YX1	15.9	0.1	Imperceptible	Negligible
YX10	15.3	0.1	Imperceptible	Negligible
YX11	14.8	Less than 0.1.	Imperceptible	Negligible
YX12	14.8	Less than 0.1.	Imperceptible	Negligible
YX13	15.5	0.1	Imperceptible	Negligible
YX14	14.6	Less than 0.1.	Imperceptible	Negligible
YX15	14.5	0.1	Imperceptible	Negligible
YX16	15.3	0.1	Imperceptible	Negligible
YX17	14.1	Less than 0.1.	Imperceptible	Negligible

\* All values have been rounded to the nearest decimal place.

**Table 5.21: PM<sub>2.5</sub> concentration during operation of the proposed development during the 2028 busiest day and the magnitude of change compared to the 2028 baseline concentration.**

Receptor	2028 busiest day*.		Change descriptor.	Effect descriptor.
	Concentration ( $\mu\text{g}/\text{m}^3$ )	Magnitude of change ( $\mu\text{g}/\text{m}^3$ ).		
YX1	10.2	0.2	Imperceptible	Negligible
YX10	9.4	0.2	Imperceptible	Negligible
YX11	8.6	0.1	Imperceptible	Negligible
YX12	8.6	0.1	Imperceptible	Negligible
YX13	9.6	0.2	Imperceptible	Negligible
YX14	8.3	Less than 0.1.	Imperceptible	Negligible

Receptor	2028 busiest day*		Change descriptor.	Effect descriptor.
	Concentration (µg/m <sup>3</sup> )	Magnitude of change (µg/m <sup>3</sup> ).		
YX15	8.9	0.1	Imperceptible	Negligible
YX16	9.2	0.1	Imperceptible	Negligible
YX17	8.3	Less than 0.1.	Imperceptible	Negligible

\* All values have been rounded to the nearest decimal place.

5.6.15 Following the classification of effects of operational phase traffic, the effects of both average and busiest day traffic at all receptors are to negligible. The effects on air quality resulting from traffic associated with the operation of the proposed development are **not significant** at all sensitive receptors near the proposed development.

ii. Inter-relationship effects

5.6.16 There are potential inter-relationship effects on ecological and amenity and recreation receptors as a result of changes to air quality during the operational phase of development. These potential impacts are considered within **Chapters 7** and **8** of this volume respectively. Inter-relationship effects on human health receptors are considered further in **Chapter 28** of this volume of the **ES**, and in **Volume 10, Chapter 2** of the **ES**.

d) Removal and reinstatement

5.6.17 The removal and reinstatement phase of the proposed development would include breaking and clearance of hardstanding and removal of buildings. Overall, the scale and nature of demolition and earthwork activities expected to be undertaken are similar to the scale and nature of these activities in the construction phase.

5.6.18 The likely scale of works would generate a similar level of traffic to the construction phase. Therefore, the air quality effects are expected to be moderate beneficial to negligible at all sensitive receptors.

5.6.19 As the dust and traffic emissions effects associated with the removal and reinstatement phase is not expected to be worse than the air quality effects associated with the construction phase (and the assessed early years (2023)), the impacts of NO<sub>2</sub> and particulate matter resulting from the removal and reinstatement phase would be **not significant**.

i. Inter-relationship effects

5.6.20 There are potential inter-relationship effects on ecological and amenity and recreation receptors as a result of changes to air quality during the removal

and reinstatement phase of development. These potential impacts are considered within **Chapters 7** and **8** of this volume respectively. There is also the potential for impacts relating to soils management on site as detailed in **Chapter 10** of this volume, to give rise to air quality effects from dust. Inter-relationship effects on human health receptors are considered further in **Chapter 28** of this volume, and in **Volume 10, Chapter 2** of the **ES**.

## 5.7 Mitigation and monitoring

5.7.1 Primary and tertiary mitigation measures, which have been accounted for as part of the assessment, are summarised in **section 5.5** of this chapter. Where other mitigation is required to reduce, or avoid a significant effect, this is referred to as secondary mitigation.

5.7.2 No further mitigation measures for the air quality are required to reduce or avoid a significant adverse effect. In addition, no monitoring of air pollutant concentrations, or dust deposition rates is proposed, given the location of the nearest sensitive receptors relative to the proposed development; the routing of traffic using the proposed development, and that no significant effects are predicted.

## 5.8 Residual effects

5.8.1 **Table 5.22, Table 5.23, and Table 5.24** present a summary of the air quality assessment. They identify the receptors likely to be impacted, the level of effect and, where the effect is deemed to be significant, the tables include the mitigation proposed and the resulting residual effect.

5.8.2 No significant adverse residual effects are predicted during the construction, operation or removal and reinstatement phases of the proposed development.

**Table 5.22: Summary of effects for the construction phase.**

Receptor	Impact	Primary or Tertiary Mitigation.	Assessment of Effects.	Additional Mitigation.	Residual Effects.
Residential Properties.	Potential amenity or health impacts from generation of particulate matter from construction activities.	As recommended in <b>CoCP</b> (Doc Ref. 8.11) based on risk assessment.	Negligible	None required.	Negligible <b>(Not significant).</b>
Residential Properties.	Emissions from additional road vehicle movements.	Site location and layout.	Negligible	None required.	Negligible <b>(Not significant).</b>

**Table 5.23: Summary of effects for both typical and busiest day operational phase.**

Receptor	Impact	Primary or Tertiary Mitigation.	Assessment of Effects.	Additional Mitigation.	Residual Effects.
Residential Properties.	Emissions from additional road vehicle movements.	Site location and layout.	Negligible.	None required.	Negligible <b>(Not significant).</b>

**Table 5.24: Summary of effects for the removal and reinstatement phase.**

Receptor	Impact	Primary or Tertiary Mitigation.	Assessment of Effects.	Additional Mitigation.	Residual Effects.
Residential Properties.	Potential amenity or health impacts from generation of particulate matter from construction activities.	As recommended in <b>CoCP</b> (Doc Ref. 8.11) based on risk assessment.	Negligible	None required.	Negligible <b>(Not significant).</b>
Residential Properties.	Emissions from additional road vehicle movements.	Site location and layout.	Negligible	None required.	Negligible <b>(Not significant).</b>

## References

- 5.1. The European Commission, Directive 2008/50/EC of the European Parliament and of the Council on ambient air quality and cleaner air for Europe (2008)
- 5.2. The European Commission, Directive 2004/107/EC of the European Parliament and of the Council relating to arsenic, cadmium, mercury, nickel and polycyclic aromatic hydrocarbons in ambient air (European Fourth Daughter Directive on Ambient Air Quality) (2004)
- 5.3. The Air Quality Standards Regulations (2010). Statutory Instrument No. 1001. The Stationary Office, 2011
- 5.4. Great Britain. Department for Environment, Food & Rural Affairs (DEFRA). The Air Quality Strategy for England, Scotland, Wales and Northern Ireland (National Air Quality Strategy). London: The Stationery Office, 2007. (Online) Available from: <https://www.gov.uk/government/publications/the-air-quality-strategy-for-england-scotland-wales-and-northern-ireland-volume-1> (Accessed 05/08/2019)
- 5.5. Department of Energy and Climate Change (2011) Overarching National Policy Statement for Energy (EN-1)
- 5.6. Department of Energy and Climate Change (2011) National Policy Statement for Nuclear Power Generation (EN-6)
- 5.7. Suffolk County Council. Suffolk Local Transport Plan 2011 – 2031. (Online) Available from: <https://www.suffolk.gov.uk/roads-and-transport/transport-planning/transport-planning-strategy-and-plans/> (Accessed July 2019)
- 5.8. East Suffolk Council. Suffolk Coastal District Council Core Strategy and Development Management Policies. 2013. (Online) Available from: <https://www.eastsuffolk.gov.uk/planning/local-plans/suffolk-coastal-local-plan/existing-local-plan/core-strategy-and-development-management-policies/> (Accessed July 2019)
- 5.9. East Suffolk Council. Suffolk Coastal Final Draft Local Plan. Suffolk. 2019. (Online) Available from: <https://www.eastsuffolk.gov.uk/assets/Planning/Suffolk-Coastal-Local-Plan/Final-Draft-Local-Plan/Final-Draft-Local-Plan.pdf> (Accessed October 2019)



- 
- 5.10. Highways England, Sustainability & Environment Appraisal LA 105 Air quality. 2019. (Online). Available at: <http://www.standardsforhighways.co.uk/ha/standards/dmr/vol11/section3/LA%20105%20Air%20quality-web.pdf> (Accessed January 2020)
- 5.11. Institute of Air Quality Management, Land use planning and development control: Planning for air quality, (2017)
- 5.12. IAQM. Guidance on the Assessment of Dust from Demolition and Construction. 2016. (Online) Available from: <https://iaqm.co.uk/text/guidance/construction-dust-2014.pdf> (Accessed April 2019)
- 5.13. IAQM. A guide to the assessment of air quality impacts on designated nature conservation sites. 2019. (Online) Available from: <https://iaqm.co.uk/text/guidance/air-quality-impacts-on-nature-sites-2019.pdf> (Accessed July 2019)
- 5.14. National Atmospheric Emissions Inventory (NAEI). Available from: <https://naei.beis.gov.uk/> (Accessed October 2019)
- 5.15. Defra (2019) Background Mapping data for local authorities, Available at: <https://uk-air.defra.gov.uk/data/iaqm-background-maps?year=2015>