

Longfield Solar Farm

Environmental Statement PINS Ref: EN010118

Volume 2

Appendix 11C: Construction Noise Modelling

Document Reference EN010118/APP/6.2

Revision Number: 1.0

February 2022

Longfield Solar Energy Farm Ltd

APFP Regulation 5(2)(a)

Planning Act 2008

Infrastructure Planning (Applications: Prescribed Forms and Procedure) Regulations 2009

Quality information

Prepared by	Checked by	Verified by	Approved by	
RF	со	YL	NT	
Graduate Acoustics Consultant	Principal Acoustics Consultant	Regional Acoustics Director	Technical Director	

Prepared for:

Longfield Solar Energy Farm Ltd

Prepared by:

AECOM UK Limited Midpoint, Alencon Link Basingstoke Hampshire RG21 7PP United Kingdom

T: +44(0)1256 310200 aecom.com

© AECOM UK Limited. All Rights Reserved.

This document has been prepared by AECOM Limited ("AECOM") for sole use of our client (the "Client") in accordance with generally accepted consultancy principles, the budget for fees and the terms of reference agreed between AECOM and the Client. Any information provided by third parties and referred to herein has not been checked or verified by AECOM, unless otherwise expressly stated in the document. No third party may rely upon this document without the prior and express written agreement of AECOM.



Table of Contents

1.	Construction Noise Modelling	1
1.1	Construction works noise	1
1.2	Construction traffic noise	2



1. Construction Noise Modelling

1.1 Construction works noise

1.1.1 Initial construction noise predictions are based on single items of plant working simultaneously at a fixed position. The predictions have not included any mitigation in the form of screening or reduction in the percentage on-time (i.e. equipment assumed to be in continuous use).

BS 5228-1	Plant	Noise	Stage					
reference.		dB(A) at 10m	3(A) at 10m Site prepar		ite preparation Installation of PV panels		Cable route trenching	
			Qty	dB(A)	Qty	dB(A)	Qty	dB(A)
C.2-10	Dozer	80	1	80		0	1	80
C.2-14	Excavator	79	1	79	1	79		0
C.12-1	Push press piling	68		0	1	68	1	68
Total Noise at 10m			;	83		79	:	80

1.1.2 The distance adjustment to construction noise levels (reference distance 10m) have followed guidance from BS 5228-1 Annex F.2.2 'Method for activity L_{Aeq,T}' using formula:

$K_h = 20 \log_{10} R/10$

where:

K_h is the distance adjustment for hard ground conditions, in decibels (dB);

R is the distance from the activity.

Distance, m	K _h , dB		
10	0		
25	8		
50	14		
75	18		
100	20		
250	28		
500	34		
750	38		
1000	40		



1.2 Construction traffic noise

1.2.1 Construction traffic noise calculations have followed guidance from BS 5228-1 Annex F.2.5 'Method for mobile plant using a regular well-defined route (e.g. haul roads)' using formula:

 $L_{Aeq, T} = L_{WA} - 33 + 10log_{10}Q - 10log_{10}V - 10log_{10}d$

where:

L_{WA} is the sound power level of the vehicle, in decibels (dB);

Q is the number of vehicles per hour;

V is the average vehicle speed, in kilometres per hour (km/h); and

d is the distance of receiving position from the centre of haul road, in metres (m).

HGV (50 per 12 hour day)		Other vehicles (330 per 12 hour day)		
L _{WA}	110	L _{WA}	99	
Q	4	Q	30	
v	50	V	50	
d	3	d	3	
L _{Aeq,1hr}	61	L _{Aeq,1hr}	59	
Total I Apr 1hr		62		

Total LAeq,1hr

63