

A1 in Northumberland: Morpeth to Ellingham

Scheme Number: TR010041

6.8 Environmental Statement – Appendix 6.5 Source Information and Assumptions for Operational Road Traffic Noise Assessment

Part B

APFP Regulation 5(2)(a)

Planning Act 2008

Infrastructure Planning (Applications: Prescribed Forms and Procedure) Regulations 2009



Infrastructure Planning

Planning Act 2008

The Infrastructure Planning (Applications: Prescribed Forms and Procedure) Regulations 2009

The A1 in Northumberland: Morpeth to Ellingham Development Consent Order 20[xx]

Environmental Statement - Appendix

Regulation Reference:	APFP Regulation 5(2)(a)
Planning Inspectorate Scheme	TR010041
Reference	
Application Document Reference	TR010041/APP/6.8
Author:	A1 in Northumberland: Morpeth to Ellingham Project Team, Highways England

Version	Date	Status of Version
Rev 0	June 2020	Application Issue



CONTENTS

SOURCE INFORMATION AND ASSUMPTIONS FOR OPERATIONAL ROAD TRAFFIC NOISE ASSESSMENT 1

TABLES

Table 6-1 - Noise Modelling Assumptions and Settings

1

Part B: Alnwick to Ellingham 6.8 Environmental Statement



SOURCE INFORMATION AND ASSUMPTIONS FOR OPERATIONAL ROAD TRAFFIC NOISE ASSESSMENT

Table 6-1 - Noise Modelling Assumptions and Settings

[1] Noise prediction methodology	The Calculation of Road Traffic Noise (CRTN) memorandum (1988), published by the Department of Transport and Welsh Office. Additional advice detailed within Annex 4: Additional advice to CRTN procedures of the DMRB Volume 11 Section 3 Part 7, HD 213/11 – Revision 1 Noise and vibration.
[2] Noise modelling software	Version 2017 (64 bit) of the CadnaA, PC based, noise modelling suite.
[3] Base mapping	Ordnance Survey (OS) MasterMap Topography Layer has been incorporated within the noise model to provide base-mapping for the area.
[4] Terrain data	For the A1 in Northumberland: Alnwick to Ellingham (Part B) alignment, topographic data have been extracted from the 3D engineering drawings.
	Immediately surrounding Part B and within the Order Limits for the DM scenarios, topographical survey data has been applied to generate 0.25 m height contours.
	For the remainder of the Study Area, Lidar data (1 m grid spacing) were downloaded from the .GOV website and imported into CadnaA, with 1 m height contours subsequently generated by the noise modelling software.
[5] Road traffic source	All roads that are unaltered by Part B, have been spatially aligned using the OS MasterMap Topography Layer.
	All new, altered and relieved roads comprising the Part B improvements, have been spatially aligned using the engineering drawings provided by WSP.
	Road heights and gradients have been determined automatically from the terrain data as created (refer to [4] above).
	The traffic data (flow, speed and proportion of heavy vehicles) have been provided for all relevant scenarios:
	- Do-minimum, year of opening (2023)
	- Do-something, design year (2038)
	- Do-minimum, year of opening (2023)
	- Do-something, design year (2038)

A1 in Northumberland: Morpeth to Ellingham Part B: Alnwick to Ellingham 6.8 Environmental Statement



	Roads with 18-hour flows of less than 1,000 in all scenarios have been excluded. Where flows fall between 1,000 and 4,000 in the 18-hour period, a low-flow correction has been applied. Speed bands have been used; all roads have been assigned one of the following speeds, as specified in IAN185/15: 97, 63, 55, 33 and 20 kph. All roads with a standard hot rolled asphalt surface have been assigned a correction of -1.0 dB where speeds are below 75 kph and -0.5 dB for speeds at or above 75 kph (equivalent to a road surface texture depth of 1.5 mm). All roads with a new low noise road surface have been assigned a correction of -3.5 dB, but only where speeds are at or above 75 kph, otherwise a correction of -1.0 dB has been applied.
[6] Bridges	Bridges have been incorporated manually into the noise model and spatially aligned based on the OS MasterMap Topography Layer and the terrain data as created (refer to [4] above). Where any road passes over a bridge, care has been taken to ensure the road sits appropriately on the bridge, rather than following the local terrain.
[7] Buildings	Building outlines have been incorporated into the noise model based on the OS MasterMap Topography Layer. A height of 8 m has been assigned universally to all buildings except those which have been identified through a review of street scene photography, to be 1-storey, for which a height of 5m has been applied. All buildings have been set to be reflective (absorption coefficient of 0), which means that these buildings potentially might reflect noise if they lie close to, and on the opposite side of the highway (i.e. opposite reflections using CRTN terminology).
[8] Ground cover	A default ground absorption coefficient of 1 has been adopted (i.e. acoustically absorbent ground cover). However, roads and buildings have been set to be acoustically reflecting.
[9] Noise levels	Unless stated otherwise, all noise levels presented in this report are in terms of L _{A10,18h} in the free-field.

© Crown copyright 2020.

You may re-use this information (not including logos) free of charge in any format or medium, under the terms of the Open Government Licence. To view this licence: visit www.nationalarchives.gov.uk /doc/open-government-licence/write to the Information Policy Team, The National Archives, Kew, London TW9 4DU, or email psi@nationalarchives.gsi.gov.uk.

This document is also available on our website at www.gov.uk /highways

If you have any enquiries about this document A1inNorthumberland@highwaysengland.co.uk or call $0300\,470\,4580^*$.

*Calls to 03 numbers cost no more than a national rate call to an 01 or 02 number and must count towards any inclusive minutes in the same way as 01 and 02 calls.

These rules apply to calls from any type of line including mobile, BT, other fixed line or payphone. Calls may be recorded or monitored.

Registered office Bridge House, 1 Walnut Tree Close, Guildford GU1 4LZ Highways England Company Limited registered in England and Wales number 09346363