


Cambridge Waste Water Treatment Plant Relocation Project Anglian Water Services Limited

Appendix 19.3: Transport Assessment Part 2

Application Document Reference: 5.4.19.3

PINS Project Reference: WW010003


APFP Regulation No. 5(2)a




Cambridge Waste Water Treatment Relocation Project Transport Assessment



Appendix G: Swept Path Analysis



Page 427 of 1013



Page 428 of 1013 1. Do not acab from this disorbin.
2. All discretions are in mindres unless otherwise shows. All levels are in minres above Ordance Datam (ADD) All dismessions are in minres unless of the should be checked on site.
3. Any drawing errors or discregancies should be brought to the attention of Medi MacCondia of the address drown in the title block.
4. All the discretion of the title block.
5. The dawing of the should be proposed for the roll high level optioneeing study for the CWMYW project.
6. The shormation is prelimitary and subject to Luther detailed design.
6. The shormation is prelimitary and subject to Luther detailed design.
6. The dawing does not include any information on proposed highway drainage and associated SUIC, existing or prosposed utilises or relimitary drainage and associated SUIC, existing or prosposed utilises or relimite externition assess that may need to associated SUIC, existing or prosposed utilises or relimite externity assess that may need to associated SUIC, existing or prosposed utilises or relimite externity assess that may need to associated SUIC, existing or prosposed utilises or relimite externity assess that the ray need to associated SUIC, existing or prosposed utilises or relimite externity assess that the ray need to associated SUIC, existing or prosposed utilises or relimine externity assess that the ray need to associate substantial substantials.


10. The dawings do not include any street lightly or other highway infrastructions which in the dawings do not include any street lightly or other highway infrastructions which in the dawings do not include any street lightly or other highway street lightly Wester MacCounter of the requirements of DRRS. Manual or Sureals as been accelerable-street and daming the street should be supposed to the design development of the spotion.

15. British of the sureal street should be supposed to the design development of the spotion. 0 Vehicle Tracking - Key to Symbols Pink shade & symbol Vehicle Tracking - Notes A. The swept path analyses shown on this drawing indicate theoretical / idealised paths that the specified whides can take, as derived using Autobeek's Vehicle Tracking software. The paths assume that the vehicle's driver will make a turn from a specific point / initial alignment, in the most effective manner. The Client / Architect should note that achievement of the idealised paths is subject to driver's anticipation of turning points, driving ability, and due care. It is therefore recommended that the area is set out and driven in real file, prior to acceptance for construction particularly if there is any concern that the idealised track may not be readily achieved. Crawler Crane (Access) Vehicle Tracking - Risks & Compliance Risks Kerb overrun 0 love every drop Cambridge Waste Water Treatment Works Relocation Temporary Access Junctions COA17 - COA18 Highways GA, Visibility Splay and Vehicle Tracking Eng check F.Case. Coordination A.M.Rawling Drawn Dwg check Approved StatuPRE Scal**4**:1500 Secu**S**yTD Drawing 100 29 75 - MMD-01-XX-DR-C-DRAFT Crawler Crane (Egress) w local insequences in the party which commissioned it and for specific purposes connected with the captionesis project only. It should not be relied upon by any other party or used for any other purpose.

We accept no responsibility for the consequences of this document being relied upon by any other party, or being used for any other purpose, or containing any error or emission which is due to an error or emission in data supplied to us by other parties.




Page 430 of 1013





Page 431 of 1013 1. Do not acab from this drowing.
2. All discretions are in motives unless otherwise shows. All levels are in metres above Ordance Datum (ADD). All directs on the state of t 1 Vehicle Tracking - Key to Symbols Pink shade & symbol denote reverse direction d red lines denote wheel / track paths Solid blue lines denote chassis paths Vehicle Tracking - Notes A The swept path analyses shown on this drawing indicate theoretical / idealised paths that the specified whides can take, as derived using Autodesk's Vehicle Tracking software. The paths assume that the vehicle's driver will make a turn from a specific point / initial alignment, in the most effective manner. The Client / Architect should note that achievement of the idealised paths is subject to driver's anticipation of turning points, driving ability, and due care. It is therefore recommended that the area is a total and driver in relific prior to acceptance for construction particularly if there is any concern that the feelisted track may not be readly schilered. Crawler Crane (Access) Vehicle Tracking - Risks & Compliance Risks Kerb overrun love every drop anglianwater . Cambridge Waste Water Treatment Works Relocation Temporary Access Junctions CA29 Highways GA, Visibility Splay and Vehicle Tracking Eng check F.Case A D Castles Coordination A.M.Rawling Drawn Dwa check Approved StatuPRE Scal**d** at **5**00 Secu**S**yTD Drawing 100 29 75 - MMD-01-XX-DR-C-DRAFT Crawler Crane (Egress) We want was constructed by any other purply which commissioned it and for specific purposes connected with the captioned project only. It should not be relied upon by any other purpose, and the purpose, and the purpose of this document being relied upon by any other purpose, or containing any error or omission which is due to an error or omission in data supplied to us by other parties.

Page 433 of 1013



Page 434 of 1013





Page 436 of 1013 1. Do not scale from this drowing.
2. All dimensions are in meries unless otherwise show. All levels are in metres above Ordance Datum (ACD). All dimensions & levels should be checked on site.
3. Any drawing errors or discrepancies should be brought to the attention of Medit MucContral at the abdress shown the site tile block.
4. Any drawing errors or discrepancies should be brought to the attention of Medit MucContral at the abdress shown in the site tile block.
4. Contral the state of the site of the initial high level splonneering study for the CWITYW project.
5. The dawing is based on OS reaging information and LIDAR data.
6. The information is prelimitary and subject to further detailed design of the information is prelimitary and subject to further detailed design of the information of the information are information on proposed highway drainage and subscited SUIDS, existing or prospect utilities or other excelling sasses that may need to associated SUIDS, existing or prospect utilities or other excelling sasses that may need to associated SUIDS, existing or prospect utilities or other excelling sasses that may need to associated SUIDS, existing or prospect utilities or other excelling sasses that may need to associated SUIDS, excelling or prospect utilities or other excelling sasses that may need to associated SUIDS, excelling or prospect utilities or other excelling sasses that may need to associated SUIDS, excelling or prospect utilities or other excelling sasses and the subscientified of the excelling sasses and excelling sass Vehicle Tracking - Key to Symbols Pink shade & symbol denote reverse direction red lines denote wheel / track paths Solid blue lines denote chassis paths Widths are limited throughout the access road Road surfacing is heavily degraded throughout the access road Vehicle Tracking - Vehicle Details General Arrangement Vehicle Tracking - Risks & Compliance High Risks
H1 Explanation of risk. A. The swept path analyses shown on this drawing indicate theoretical / idealised paths that the specified whiches can take, as derived using Audoesk's Vehicle Tracking others. The paths assume that the vehicle's driver will make a turn from a specific point / initial alignment, in the most effective manner. The Clentr / Architect should note that schievement of the desland paths is subject to their anticipation of turning points, driving ability, and due care. It is therefore recommended that the areas is so that of driven in real file, prof to accordance for construction, particularly if there is any concern that the idealised track may not be readly schieved. 160 160 love every drop anglianwater . Cambridge Waste Water Treatment Works Relocation Temporary Access Junctions CA26 Highways GA, Visibility Splay and Vehicle Tracking Eng check F.Case Coordination A.M.Rawling Drawn Dwa check Approved StatuPRE Secu**S**yTD Scal**d** a **500**

Visibility Plan

Drawing 100 29 75 - MMD-01-XX-DR-C-DRAFT

w local measuration I.

This document is it issued for the party which commissioned it and for specific purposes connected with the captioned project only. It should not be relied upon by any other party or used for any other purpose.

We accept no responsibility for the consequences of this document being relied upon by any other party, or being used for any other purpose, or containing any error or emission which is due to an error or emission in data supplied to us by other parties.

Page 437 of 1013 1. Do not acade from this drawing.
2. All dimensions are in morters unless otherwise shown. All levels are in metres above.
2. All dimensions are in morters unless otherwise shown. All levels are in metres above.
3. Any drawing errors or discregaments all levels should be checked on site.
3. Any drawing errors or discregaments about be brought to the attention of Mott.
3. Any drawing errors or discregaments about be brought to the attention of Mott.
4. Considering the second of the second in the second of the discregaments of t Vehicle Tracking - Key to Symbols Pink shade & symbol denote reverse direction 0 d red lines denote wheel / track paths Solid blue lines denote chassis paths Vehicle Tracking - Notes A The swept path analyses shown on this drawing indicate theoretical / idealised paths that the specified whides can take, as derived using Autodesk's Vehicle Tracking software. The paths assume that the vehicle's driver will make a turn from a specific point / initial alignment, in the most effective manner. The Client / Architect should note that achievement of the idealised paths is subject to driver's anticipation of turning points, driving ability, and due care. It is therefore recommended that the area is a total and driver in relific prior to acceptance for construction particularly if there is any concern that the feelisted track may not be readly schilered. Crawler Crane (Access) Vehicle Tracking - Risks & Compliance Risks Kerb overrun love every drop Cambridge Waste Water Treatment Works Relocation Temporary Access Junctions CA26 Highways GA, Visibility Splay and Vehicle Tracking Eng check F.Case. Coordination A.M.Rawling Drawn Dwa check Approved StatuPRE Secu**S**yTD Scal**d** at **5**00 Drawing 100 29 75 - MMD-01-XX-DR-C-DRAFT Crawler Crane (Egress) Water maccurain.

This document is issued for the party which commissioned it and for specific purposes connected with the captioned project only. It should not be relied upon by any other party or used for any other purpose.

We accept no responsibility for the consequences of this document being relied upon by any other party, or being used for any other purpose, or containing any error or omission which is due to an error or omission in data supplied to us by other parties.

Page 438 of 1013 1. Do not acade from this drawing.
2. All discremisors are in motives unless otherwise shown. All levels are in metres above.
2. All discremisors are in motives unless otherwise shown. All levels are in metres above.
3. Any drawing errors or discregancies should be brought to the attention of Mott.
3. Any drawing errors or discregancies should be brought to the attention of World
3. Any drawing errors or discregancies should be brought to the attention of World
4. Consideration of the state of Vehicle Tracking - Key to Symbols Pink shade & symbol denote reverse direction 0 d red lines denote wheel / track paths Solid blue lines denote chassis paths Vehicle Tracking - Notes A The swept path analyses shown on this drawing indicate theoretical / idealised paths that the specified whides can take, as derived using Autodesk's Vehicle and Tracking software. The paths saveme that the vehicle's driver will make a turn from a specific point / initial alignment, in the most effective manner. The Client / Architect should note that achievement of the idealised paths is subject to driver's anticipation of turning points, driving ability, and due care. It is therefore recommended that the area is a total and driver in relific prior to acceptance for construction particularly if there is any concern that the feelisted track may not be readly schilered. Low Loader (Access) Vehicle Tracking - Risks & Compliance Risks Kerb overrun 0 love every drop Cambridge Waste Water Treatment Works Relocation Temporary Access Junctions CA26 Highways GA, Visibility Splay and Vehicle Tracking Eng check F.Case. Coordination A.M.Rawling Drawn Dwa check Approved StatuPRE Secu**S**yTD Scal**d** at **5**00 Drawing 100 29 75 - MMD-01-XX-DR-C-DRAFT Water maccurain.

This document is issued for the party which commissioned it and for specific purposes connected with the captioned project only. It should not be relied upon by any other party or used for any other purpose.

We accept no responsibility for the consequences of this document being relied upon by any other party, or being used for any other purpose, or containing any error or omission which is due to an error or omission in data supplied to us by other parties. Low Loader (Egress)

Page 439 of 1013 1. Do not acab from this disorbin.
2. All discretions are in mindres unless otherwise shows. All levels are in minres above Ordance Datam (ADD) All dismessions are in minres unless of the should be checked on site.
3. Any drawing errors or discregancies should be brought to the attention of Medi MacCondia of the address drown in the title block.
4. All the discretion of the title block.
5. The dawing of the should not be from the title block.
6. The dawing to based on OS mapping information and LIDAR data.
6. The information is prelimitary and subject to further detailed design.
6. The dawing does not include any information on proposed highway drainage and associated SUIC, existing or processed utilises or other exciting sasses that the ray need to associated SUIC, existing or processed utilises or other exciting sasses that the ray need to associated SUIC, existing or processed utilises or other exciting sasses that the ray need to associated SUIC, existing or processed utilises or other exciting sasses that the ray need to associated SUIC, existing or processed utilises or other exciting sasses that the ray need to associated SUIC, existing or processed utilises or other exciting sasses that the ray need to associated SUIC, existing or processed utilises or other exciting sasses where the respective sasses are not exhaustered also per 1.0 as exceptable to the relevant staked-richers.
1. The design is based on the requirements of DRRS. Manual or Surses has been cache exceptable or the respiratories as other exceptable or the respiratories as other exceptable or the respiratories of the design development of this gotion.

1.5. Proceeding and the survey of the design of the design of evolopment of the spotion. e: Road widths are limited throughout Vehicle Tracking - Key to Symbols Pink shade & symbol denote reverse direction Solid blue lines denote chassis paths Vehicle Tracking - Vehicle Details Layout of bellmouth subject to more detailed iscussions with the LHA over vehicle numbers and propriate Construction Traffic mitigation measures General Arrangement Vehicle Tracking - Risks & Compliance High Risks
H1 Explanation of risk. A. The swept path analyses shown on this drawing indicate theoretical / idealised paths that the specified whicks can take, as derived using Audodes's Vehicles Tracking software. The paths assume that the vehicles driver will make a turn from a specific point / initial alignment, in the most effective manner. The Chert / Architect should note that schewener of the dealester paths a subject to driver's anticipation of turning points, driving ability, and cue cans. It is therefore recommended that the area is set out and driven in self-like, prof to bacceptance from the commended that the area is set out and driven in self-like, prof to bacceptance from the commended that the area is set out and driven in self-like, prof to bacceptance from the commended profit is the self-like of the self-like o 160-160 love every drop anglianwater a Cambridge Waste Water Treatment Works Relocation Temporary Access Junctions COA13 Highways GA, Visibility Splay and Vehicle Tracking Horizontal visibility splay 2.4m x 160m Requires no further speed restrictions Eng check F.Case Coordination A.M.Raw Drawn Dwa check Approved Statu**PRE** Secu**S**yTD Scal**d** at **500** Drawing 100 29 75 - MMD-01-XX-DR-C-DRAFT

Visibility Plan

Vacci inscriptions.

It should not be relied upon by any other party which commissioned it and for specific purposes connected with the captioned project only. It should not be relied upon by any other party or used for any other purpose.


We accept no responsibility for the consequences of this document being relied upon by any other party, or being used for any other purpose, or containing any error or omission which is due to an error or omission in data supplied to us by other parties.

Page 440 of 1013 1. Do not acate from this drowing.
2. All discretions are in motives unless otherwise shows. All levels are in metres above Ordanico Disturni ACDD, All directions are less than the control of Control of the Control of Control Vehicle Tracking - Key to Symbols Pink shade & symbol denote reverse direction 0 Solid blue lines denote chassis paths ehide Tracking - Notes A. The swept path analyses shown on this drawing indicate theoretical / idealised paths that the specified whides can take, as derived using Autobeek's Vehicle Tracking slower. The paths assume that the vehicle's driver vill make a turn from a specific point / initial alignment, in the most effective manner. The Client / Architect should note that achievement of the idealised paths is subject to driver's anticipation of turning points, driving ability, and due care. It is therefore recommended that the area is set out and driven in real file, prior to acceptance for construction particularly if there is any concern that the idealised track may not be readily achieved. Crawler Crane (Access) Vehicle Tracking - Risks & Compliance Risks Kerb overrun love every drop Cambridge Waste Water Treatment Works Relocation Temporary Access Junctions COA13 Highways GA, Visibility Splay and Vehicle Tracking Eng check F.Case Coordination A.M.Raw Drawn Dwa check Approved StatuPRE Scal**4**:1500 Secu**S**yTD Drawing 100 29 75 - MMD-01-XX-DR-C-DRAFT Crawler Crane (Egress) Vacci Mescuress |


This document is it issued for the party which commissioned it and for specific purposes connected with the captioned project only. It should not be relied upon by any other party or used for any other purpose.

We accept no responsibility for the consequences of this document being relied upon by any other party, or being used for any other purpose, or containing any error or emission which is due to an error or emission in data supplied to us by other parties.


Page 442 of 1013




Page 443 of 1013




Page 444 of 1013




Page 445 of 1013





Page 446 of 1013




Page 447 of 1013











Page 451 of 1013





Page 453 of 1013 Vehicle Tracking - Notes A. The swept path analyses shown on this drawing indicate theoretical / idealised paths that the specified vehicles can take, as derived using Audiodes's Vehicle Tracking software. The paths assume that the vehicle's other will make a turn from a specific point / initial alignment, in the most effective manner. The Client / Architect should note that achievement of the idealised paths is subject to drive's anticipation of turning points, driving ability, and due care. It is theretor concernmented that the area is set out and driven in real file, prior to acceptance for construction, particularly if there is any concern that the idealised track may not be readly achieved. 1. Do not scale from this drowing.
2. All dimensions are in meriters upters otherwise show. All levels are in metres above Ordance Datum (ACD). All dimensions & levels should be checked on site.
3. Any drawing errors or discrepancies should be brought to the attention of Medit MucContral at the abdress shown in the title block.
4. Any drawing errors or discrepancies should be brought to the attention of Medit MucContral at the abdress shown in the title block.
5. The drawing is based on OS reagong information and LIDAR data.
6. The information is prelimitary and subject to the title block data.
6. The information is prelimitary and subject to the title detailed design.
6. The drawing does not include any information on proposed highway drainage and suscitated SUIDS, existing or prospect utilities or other exciting sasses the titrary need to associated SUIDS, existing or prospect utilities or other exciting sasses that may need to associated SUIDS, existing or prospect utilities or other exciting sasses that may need to associated SUIDS, existing or prospect utilities or other exciting sasses that may need to associated SUIDS, existing or prospect utilities or other exciting sasses that may need to associated SUIDS, exciting or prospect utilities or other exciting sasses that may need to associated SUIDS, exciting or prospect utilities or other exciting sasses with the relievent state/exciter.


10. The design acquires works to the public highway and would require further discussions with the relievent state/exciter.


11. The design assumes an embrachment also port of its acceptable to the relievent state-in-excited.


12. The design public sections of the prospinement of DRBs. Manual for Street has been acceptable of the relieve of the company or development of this control.


15. ShAMMON WIGHT TREE READ MI OFFICURED on with the Technical Memo. Vehicle Tracking - Key to Symbols Low Loader (Access) Vehicle Tracking - Risks & Compliance Kerb overrun love every drop anglianwater o 0 Cambridge Waste Water Treatment Works Relocation Temporary Access Junctions CA16 Highways GA, Visibility Splay and Vehicle Tracking Eng check F.Case Coordination A.M.Raw Drawn Dwg chec SecuS/TD Scal**4**:1500 Drawing 1092875-MMD-01-XX-DR-C-DRAFT Vacci resources it is issued for the party which commissioned it and for specific purposes connected with the captioned project only. It should not be reflect upon by any other party or used for any other purpose.

We accept no responsibility for the consequences of this document being reflect upon by any other party, or being used for any other purpose, or containing any error or emission which is due to an error or emission in data supplied to us by other parties. Low Loader (Egress)













Page 460 of 1013



Page 461 of 1013




Page 462 of 1013




Page 463 of 1013



Page 464 of 1013



Page 465 of 1013



Page 466 of 1013











Page 471 of 1013



Page 472 of 1013


























Page 482 of 1013



Page 483 of 1013



Page 484 of 1013



Page 485 of 1013



Page 486 of 1013



Page 487 of 1013



Page 488 of 1013



50m

102375-MMD-01-XX-DR-C-DRAFT

w local measuration I.

This document is it issued for the party which commissioned it and for specific purposes connected with the captioned project only. It should not be relied upon by any other party or used for any other purpose.

We accept no responsibility for the consequences of this document being relied upon by any other party, or being used for any other purpose, or containing any error or emission which is due to an error or emission in data supplied to us by other parties.

1:250

50m

PRE

102375-MMD-01-XX-DR-C-DRAFT


P1


ŚTD

w local insequences in the party which commissioned it and for specific purposes connected with the captionesis project only. It should not be relied upon by any other party or used for any other purpose.


We accept no responsibility for the consequences of this document being relied upon by any other party, or being used for any other purpose, or containing any error or emission which is due to an error or emission in data supplied to us by other parties.





























The ExA:

Construction traffic routes – safety


At Appendix G of the TA [AS-108] there are swept path analyses of the J34 on-slip. Please provide:

- a. a swept path analysis for the off-slip junction with the A14 overbridge, including for tipper trucks; and
- b. commentary on whether construction vehicles would be able to safely turn left or right from the J34 off-slip in the event that southbound queuing to the J34 on-slip extends close to or beyond (to the north of) the junction of the J34 off-slip and the A14 overbridge (for example when concrete pouring / directional drilling works take place during the peak periods).

The Applicant has produced these drawings. The Applicant's commentary for these swept paths is as follows:

There are no issues noted for an articulated vehicle (maximum vehicle size expected at site) to complete the left and right turn from the offslip onto Horningsea Road. It is noted that for both manoeuvres, articulated vehicles would need to encroach slightly into the opposite lane to complete the manoeuvres. In spite of this, there is no risk of collision with vehicles from opposite lanes when turning from the offslip as the traffic signal sequence at the junction ensures that when the traffic signals on the offslip are green, traffic signals on other arms would be red. In the event that southbound queuing on A14 overbridge from the on-slip extends close to or beyond the junction of the J34 offslip and the A14 overbridge, articulated vehicles would not be able to complete the right turn from the offslip due to lack of space. The left turn from the offslip onto Horningsea Road northbound north of J34 can be completed as vehicles are not expected to queue in front of the stop line on Horningsea Road southbound leading towards the offslip/A14 overbridge. Therefore, even if an articulated vehicle were to encroach on the opposite lane, there would be no traffic present on that lane owing to the location of the stop line.

Page 506 of 1013



Page 507 of 1013 Do not scale from this drawing.
 All dimensions are in metres unless otherwise shown. All levels are in metres above Ordnance Datum (AOD). All dimensions & levels should be checked on site.
 Any drawing errors or discrepancies should be brought to the attention of Mott MacDonald at the address shown in the title block. . DRAWING MUST BE READ IN COLOUR hicle Tracking - Key to Symbols Solid blue lines denote chassis paths -Vehicle Tracking - Vehicle Details 0000000 ehicle Tracking - Risks & Compliance Moderate Risks M1 Vehicle must overrun opposite lane to exit car park. Vehicle Tracking - Notes A. The swept path analyses shown on this drawing indicate theoretical / idealised A. The sweet path analyses shown on this drawing indicate theoretical /idealised paths that the specified vehicles and take, as derived using Autodesk's Vehicle Tracking software. The paths assume that the vehicle's driver will make a turn. A child contained the contained that the vehicle software will make a turn. A child cath found to the tall achievement of the idealised paths is subject to driver's anticipation of turning points, driving ability, and due care. It is therefore recommended that the area is set out and of when in real life, prior to acceptance for construction, particularly if there is any concern that the idealised track may not be readily achieved. Reference drawings Vehicle Entering Car Park Mott MacDonald 22 Station Road Cambridge, CB1 2JD MOTT M MACDONALD United Kingdom T +44 (0)1223 463 500 F +44 (0)1223 461 007 W mottmac.com love every drop anglianwater Cambridge Waste Water Treatment Works Relocation Site Access and Visitor Car Park Coach Access to Visitor's Car Park Designed J.Reeve JR Eng check W.Tong LWR Coordination A.M.Rawlings L.W.Russell Dwg check J.D.Seaston Scale at A1 1:250 PRE STD Vehicle Exiting Car Park hich commissioned it and for specific purposes connected with the captioned project only. It should not be relied upon by any other party or used for any other purpose. sequences of this document being relied upon by any other party, or being used for any other purpose, or containing any error or omission which is due to an error or omission in data supplied to us by other party. 102375-MMD-01-XX-DR-C-1142 CUlsers/RUS46566/Mott MacDonald/CWWTWR Highway Access - Project - CAD (Civils Design)(2.1 Issued Drawings (Main Site Works)(102375-MMD-01-XX-DR-C-1142_P1.dwg Dec 14, 2023 - 2-23AM RUS46566

Cambridge Waste Water Treatment Relocation Project Transport Assessment



Appendix H: Discovery Centre TRICS® Data

Page 509 of 1013

TRICS 7.9.2 180622 B20.49 Database right of TRICS Consortium Limited, 2022. All rights reserved Thursday 04/08/22 Page 1

Mott MacDonald Fleet Place London Licence No: 704113

Calculation Reference: AUDIT-704113-220804-0830

TRIP RATE CALCULATION SELECTION PARAMETERS:

Land Use : 07 - LEISURE

Category : I - ART GALLERIES/MUSEUMS/EXHIBITIONS

MULTI-MODAL TOTAL VEHICLES

Selected regions and areas:

16 ULSTER (REPUBLIC OF IRELAND)

DN DONEGAL 1 days

This section displays the number of survey days per TRICS® sub-region in the selected set

Primary Filtering selection:

This data displays the chosen trip rate parameter and its selected range. Only sites that fall within the parameter range are included in the trip rate calculation.

Parameter: Gross floor area
Actual Range: 750 to 750 (units: sqm)
Range Selected by User: 200 to 5000 (units: sqm)

Parking Spaces Range: All Surveys Included

Public Transport Provision:

Selection by: Include all surveys

Date Range: 01/01/14 to 23/11/19

This data displays the range of survey dates selected. Only surveys that were conducted within this date range are included in the trip rate calculation.

Selected survey days:

Wednesday 1 days

This data displays the number of selected surveys by day of the week.

Selected survey types:

Manual count 1 days
Directional ATC Count 0 days

This data displays the number of manual classified surveys and the number of unclassified ATC surveys, the total adding up to the overall number of surveys in the selected set. Manual surveys are undertaken using staff, whilst ATC surveys are undertaking using machines.

1

1

Selected Locations:

Edge of Town Centre

This data displays the number of surveys per main location category within the selected set. The main location categories consist of Free Standing, Edge of Town, Suburban Area, Neighbourhood Centre, Edge of Town Centre, Town Centre and Not Known.

Selected Location Sub Categories:

High Street

This data displays the number of surveys per location sub-category within the selected set. The location sub-categories consist of Commercial Zone, Industrial Zone, Development Zone, Residential Zone, Retail Zone, Built-Up Zone, Village, Out of Town, High Street and No Sub Category.

Secondary Filtering selection:

Use Class:

F1(c) 1 days

This data displays the number of surveys per Use Class classification within the selected set. The Use Classes Order 2005 has been used for this purpose, which can be found within the Library module of TRICS®.

Population within 500m Range:

All Surveys Included

Page 510 of 1013

TRICS 7.9.2 180622 B20.49 Database right of TRICS Consortium Limited, 2022. All rights reserved Thursday 04/08/22 Page 2

Mott MacDonald Fleet Place London Licence No: 704113

Secondary Filtering selection (Cont.):

Population within 1 mile:

1,001 to 5,000 1 days

This data displays the number of selected surveys within stated 1-mile radii of population.

Population within 5 miles:

5,001 to 25,000

1 days

This data displays the number of selected surveys within stated 5-mile radii of population.

Car ownership within 5 miles:

0.6 to 1.0

1 days

This data displays the number of selected surveys within stated ranges of average cars owned per residential dwelling, within a radius of 5-miles of selected survey sites.

Travel Plan:

No

1 days

This data displays the number of surveys within the selected set that were undertaken at sites with Travel Plans in place, and the number of surveys that were undertaken at sites without Travel Plans.

PTAL Rating:

No PTAL Present

1 days

This data displays the number of selected surveys with PTAL Ratings.

Page 511 of 1013

TRICS 7.9.2 180622 B20.49 Database right of TRICS Consortium Limited, 2022. All rights reserved Thursday 04/08/22 Page 3

Mott MacDonald Fleet Place London Licence No: 704113

LIST OF SITES relevant to selection parameters

1 DN-07-I-02 COUNTY MUSEUM DONEGAL

HIGH ROAD LETTERKENNY BALLYBOE GLENCAR Edge of Town Centre High Street

Total Gross floor area: 750 sqm

Survey date: WEDNESDAY 10/10/18 Survey Type: MANUAL

This section provides a list of all survey sites and days in the selected set. For each individual survey site, it displays a unique site reference code and site address, the selected trip rate calculation parameter and its value, the day of the week and date of each survey, and whether the survey was a manual classified count or an ATC count.

MANUALLY DESELECTED SITES

Site Ref	Reason for Deselection	
DU-07-I-01	Location unsuitable	
ES-07-I-01	Location unsuitable	

Page 4

Mott MacDonald Fleet Place London Licence No: 704113

TRIP RATE for Land Use 07 - LEISURE/I - ART GALLERIES/MUSEUMS/EXHIBITIONS

MULTI-MODAL TOTAL VEHICLES
Calculation factor: 100 sqm
BOLD print indicates peak (busiest) period

Total People to Total Vehicles ratio (all time periods and directions): 1.88

		ARRIVALS			DEPARTURES		TOTALS			
	No.	Ave.	Trip	No.	Ave.	Trip	No.	Ave.	Trip	
Time Range	Days	GFA	Rate	Days	GFA	Rate	Days	GFA	Rate	
00:00 - 01:00										
01:00 - 02:00										
02:00 - 03:00										
03:00 - 04:00										
04:00 - 05:00										
05:00 - 06:00										
06:00 - 07:00										
07:00 - 08:00										
08:00 - 09:00										
09:00 - 10:00	1	750	0.267	1	750	0.133	1	750	0.400	
10:00 - 11:00	1	750	0.000	1	750	0.133	1	750	0.133	
11:00 - 12:00	1	750	0.000	1	750	0.000	1	750	0.000	
12:00 - 13:00	1	750	0.133	1	750	0.000	1	750	0.133	
13:00 - 14:00	1	750	0.133	1	750	0.133	1	750	0.266	
14:00 - 15:00	1	750	0.400	1	750	0.267	1	750	0.667	
15:00 - 16:00	1	750	0.533	1	750	0.267	1	750	0.800	
16:00 - 17:00	1	750	0.133	1	750	0.667	1	750	0.800	
17:00 - 18:00	1	750	0.000	1	750	0.133	1	750	0.133	
18:00 - 19:00										
19:00 - 20:00										
20:00 - 21:00										
21:00 - 22:00										
22:00 - 23:00										
23:00 - 24:00										
Total Rates:			1.599			1.733			3.332	

This section displays the trip rate results based on the selected set of surveys and the selected count type (shown just above the table). It is split by three main columns, representing arrivals trips, departures trips, and total trips (arrivals plus departures). Within each of these main columns are three sub-columns. These display the number of survey days where count data is included (per time period), the average value of the selected trip rate calculation parameter (per time period), and the trip rate result (per time period). Total trip rates (the sum of the column) are also displayed at the foot of the table.

To obtain a trip rate, the average (mean) trip rate parameter value (TRP) is first calculated for all selected survey days that have count data available for the stated time period. The average (mean) number of arrivals, departures or totals (whichever applies) is also calculated (COUNT) for all selected survey days that have count data available for the stated time period. Then, the average count is divided by the average trip rate parameter value, and multiplied by the stated calculation factor (shown just above the table and abbreviated here as FACT). So, the method is: COUNT/TRP*FACT. Trip rates are then rounded to 3 decimal places.

The survey data, graphs and all associated supporting information, contained within the TRICS Database are published by TRICS Consortium Limited ("the Company") and the Company claims copyright and database rights in this published work. The Company authorises those who possess a current TRICS licence to access the TRICS Database and copy the data contained within the TRICS Database for the licence holders' use only. Any resulting copy must retain all copyrights and other proprietary notices, and any disclaimer contained thereon.

The Company accepts no responsibility for loss which may arise from reliance on data contained in the TRICS Database. [No warranty of any kind, express or implied, is made as to the data contained in the TRICS Database.]

Parameter summary

Trip rate parameter range selected: 750 - 750 (units: sqm) Survey date date range: 01/01/14 - 23/11/19

Number of weekdays (Monday-Friday): 1
Number of Saturdays: 0
Number of Sundays: 0
Surveys automatically removed from selection: 0
Surveys manually removed from selection: 2

This section displays a quick summary of some of the data filtering selections made by the TRICS® user. The trip rate calculation parameter range of all selected surveys is displayed first, followed by the range of minimum and maximum survey dates selected by the user. Then, the total number of selected weekdays and weekend days in the selected set of surveys are show. Finally, the number of survey days that have been manually removed from the selected set outside of the standard filtering procedure are displayed.

Licence No: 704113 Mott MacDonald Fleet Place London

TRIP RATE for Land Use 07 - LEISURE/I - ART GALLERIES/MUSEUMS/EXHIBITIONS

MULTI-MODAL VEHICLE OCCUPANTS

Calculation factor: 100 sqm

BOLD print indicates peak (busiest) period

		ARRIVALS			DEPARTURES	3	TOTALS			
	No.	Ave.	Trip	No.	Ave.	Trip	No.	Ave.	Trip	
Time Range	Days	GFA	Rate	Days	GFA	Rate	Days	GFA	Rate	
00:00 - 01:00										
01:00 - 02:00										
02:00 - 03:00										
03:00 - 04:00										
04:00 - 05:00										
05:00 - 06:00										
06:00 - 07:00										
07:00 - 08:00										
08:00 - 09:00										
09:00 - 10:00	1	750	0.267	1	750	0.133	1	750	0.400	
10:00 - 11:00	1	750	0.000	1	750	0.133	1	750	0.133	
11:00 - 12:00	1	750	0.000	1	750	0.000	1	750	0.000	
12:00 - 13:00	1	750	0.133	1	750	0.000	1	750	0.133	
13:00 - 14:00	1	750	0.267	1	750	0.133	1	750	0.400	
14:00 - 15:00	1	750	0.533	1	750	0.533	1	750	1.066	
15:00 - 16:00	1	750	0.933	1	750	0.533	1	750	1.466	
16:00 - 17:00	1	750	0.133	1	750	0.800	1	750	0.933	
17:00 - 18:00	1	750	0.000	1	750	0.133	1	750	0.133	
18:00 - 19:00										
19:00 - 20:00										
20:00 - 21:00										
21:00 - 22:00										
22:00 - 23:00										
23:00 - 24:00										
Total Rates:	2.266 2.398				2.398			4.664		

This section displays the trip rate results based on the selected set of surveys and the selected count type (shown just above the table). It is split by three main columns, representing arrivals trips, departures trips, and total trips (arrivals plus departures). Within each of these main columns are three sub-columns. These display the number of survey days where count data is included (per time period), the average value of the selected trip rate calculation parameter (per time period), and the trip rate result (per time period). Total trip rates (the sum of the column) are also displayed at the foot of the table.

To obtain a trip rate, the average (mean) trip rate parameter value (TRP) is first calculated for all selected survey days that have count data available for the stated time period. The average (mean) number of arrivals, departures or totals (whichever applies) is also calculated (COUNT) for all selected survey days that have count data available for the stated time period. Then, the average count is divided by the average trip rate parameter value, and multiplied by the stated calculation factor (shown just above the table and abbreviated here as FACT). So, the method is: COUNT/TRP*FACT. Trip rates are then rounded to 3 decimal places.

Mott MacDonald Fleet Place London Licence No: 704113

TRIP RATE for Land Use 07 - LEISURE/I - ART GALLERIES/MUSEUMS/EXHIBITIONS

MULTI-MODAL PEDESTRIANS Calculation factor: 100 sqm

BOLD print indicates peak (busiest) period

		ARRIVALS		[DEPARTURES			TOTALS		
	No.	Ave.	Trip	No.	Ave.	Trip	No.	Ave.	Trip	
Time Range	Days	GFA	Rate	Days	GFA	Rate	Days	GFA	Rate	
00:00 - 01:00										
01:00 - 02:00										
02:00 - 03:00										
03:00 - 04:00										
04:00 - 05:00										
05:00 - 06:00										
06:00 - 07:00										
07:00 - 08:00										
08:00 - 09:00										
09:00 - 10:00	1	750	0.000	1	750	0.000	1	750	0.000	
10:00 - 11:00	1	750	0.400	1	750	0.400	1	750	0.800	
11:00 - 12:00	1	750	0.000	1	750	0.000	1	750	0.000	
12:00 - 13:00	1	750	0.000	1	750	0.000	1	750	0.000	
13:00 - 14:00	1	750	0.400	1	750	0.133	1	750	0.533	
14:00 - 15:00	1	750	0.000	1	750	0.000	1	750	0.000	
15:00 - 16:00	1	750	0.000	1	750	0.267	1	750	0.267	
16:00 - 17:00	1	750	0.000	1	750	0.000	1	750	0.000	
17:00 - 18:00	1	750	0.000	1	750	0.000	1	750	0.000	
18:00 - 19:00										
19:00 - 20:00										
20:00 - 21:00										
21:00 - 22:00										
22:00 - 23:00										
23:00 - 24:00										
Total Rates:	otal Rates: 0.800 0.800 1.600									

This section displays the trip rate results based on the selected set of surveys and the selected count type (shown just above the table). It is split by three main columns, representing arrivals trips, departures trips, and total trips (arrivals plus departures). Within each of these main columns are three sub-columns. These display the number of survey days where count data is included (per time period), the average value of the selected trip rate calculation parameter (per time period), and the trip rate result (per time period). Total trip rates (the sum of the column) are also displayed at the foot of the table.

To obtain a trip rate, the average (mean) trip rate parameter value (TRP) is first calculated for all selected survey days that have count data available for the stated time period. The average (mean) number of arrivals, departures or totals (whichever applies) is also calculated (COUNT) for all selected survey days that have count data available for the stated time period. Then, the average count is divided by the average trip rate parameter value, and multiplied by the stated calculation factor (shown just above the table and abbreviated here as FACT). So, the method is: COUNT/TRP*FACT. Trip rates are then rounded to 3 decimal places.

Mott MacDonald Fleet Place London Licence No: 704113

TRIP RATE for Land Use 07 - LEISURE/I - ART GALLERIES/MUSEUMS/EXHIBITIONS

MULTI-MODAL TOTAL PEOPLE Calculation factor: 100 sqm

BOLD print indicates peak (busiest) period

Total People to Total Vehicles ratio (all time periods and directions): 1.88

		ARRIVALS		[DEPARTURES		TOTALS			
	No.	Ave.	Trip	No.	Ave.	Trip	No.	Ave.	Trip	
Time Range	Days	GFA	Rate	Days	GFA	Rate	Days	GFA	Rate	
00:00 - 01:00										
01:00 - 02:00										
02:00 - 03:00										
03:00 - 04:00										
04:00 - 05:00										
05:00 - 06:00										
06:00 - 07:00										
07:00 - 08:00										
08:00 - 09:00										
09:00 - 10:00	1	750	0.267	1	750	0.133	1	750	0.400	
10:00 - 11:00	1	750	0.400	1	750	0.533	1	750	0.933	
11:00 - 12:00	1	750	0.000	1	750	0.000	1	750	0.000	
12:00 - 13:00	1	750	0.133	1	750	0.000	1	750	0.133	
13:00 - 14:00	1	750	0.667	1	750	0.267	1	750	0.934	
14:00 - 15:00	1	750	0.533	1	750	0.533	1	750	1.066	
15:00 - 16:00	1	750	0.933	1	750	0.800	1	750	1.733	
16:00 - 17:00	1	750	0.133	1	750	0.800	1	750	0.933	
17:00 - 18:00	1	750	0.000	1	750	0.133	1	750	0.133	
18:00 - 19:00										
19:00 - 20:00										
20:00 - 21:00										
21:00 - 22:00										
22:00 - 23:00										
23:00 - 24:00										
Total Rates:			3.066			3.199		6.265		

This section displays the trip rate results based on the selected set of surveys and the selected count type (shown just above the table). It is split by three main columns, representing arrivals trips, departures trips, and total trips (arrivals plus departures). Within each of these main columns are three sub-columns. These display the number of survey days where count data is included (per time period), the average value of the selected trip rate calculation parameter (per time period), and the trip rate result (per time period). Total trip rates (the sum of the column) are also displayed at the foot of the table.

To obtain a trip rate, the average (mean) trip rate parameter value (TRP) is first calculated for all selected survey days that have count data available for the stated time period. The average (mean) number of arrivals, departures or totals (whichever applies) is also calculated (COUNT) for all selected survey days that have count data available for the stated time period. Then, the average count is divided by the average trip rate parameter value, and multiplied by the stated calculation factor (shown just above the table and abbreviated here as FACT). So, the method is: COUNT/TRP*FACT. Trip rates are then rounded to 3 decimal places.

Mott MacDonald Fleet Place London Licence No: 704113

TRIP RATE for Land Use 07 - LEISURE/I - ART GALLERIES/MUSEUMS/EXHIBITIONS

MULTI-MODAL CARS Calculation factor: 100 sqm

BOLD print indicates peak (busiest) period

	ARRIVALS			[DEPARTURES	5	TOTALS			
	No.	Ave.	Trip	No.	Ave.	Trip	No.	Ave.	Trip	
Time Range	Days	GFA	Rate	Days	GFA	Rate	Days	GFA	Rate	
00:00 - 01:00				-			_			
01:00 - 02:00										
02:00 - 03:00										
03:00 - 04:00										
04:00 - 05:00										
05:00 - 06:00										
06:00 - 07:00										
07:00 - 08:00										
08:00 - 09:00										
09:00 - 10:00	1	750	0.267	1	750	0.133	1	750	0.400	
10:00 - 11:00	1	750	0.000	1	750	0.133	1	750	0.133	
11:00 - 12:00	1	750	0.000	1	750	0.000	1	750	0.000	
12:00 - 13:00	1	750	0.133	1	750	0.000	1	750	0.133	
13:00 - 14:00	1	750	0.133	1	750	0.133	1	750	0.266	
14:00 - 15:00	1	750	0.400	1	750	0.267	1	750	0.667	
15:00 - 16:00	1	750	0.533	1	750	0.267	1	750	0.800	
16:00 - 17:00	1	750	0.133	1	750	0.667	1	750	0.800	
17:00 - 18:00	1	750	0.000	1	750	0.133	1	750	0.133	
18:00 - 19:00										
19:00 - 20:00										
20:00 - 21:00										
21:00 - 22:00										
22:00 - 23:00										
23:00 - 24:00										
Total Rates:	s: 1.599 1.733 3.33									

This section displays the trip rate results based on the selected set of surveys and the selected count type (shown just above the table). It is split by three main columns, representing arrivals trips, departures trips, and total trips (arrivals plus departures). Within each of these main columns are three sub-columns. These display the number of survey days where count data is included (per time period), the average value of the selected trip rate calculation parameter (per time period), and the trip rate result (per time period). Total trip rates (the sum of the column) are also displayed at the foot of the table.

To obtain a trip rate, the average (mean) trip rate parameter value (TRP) is first calculated for all selected survey days that have count data available for the stated time period. The average (mean) number of arrivals, departures or totals (whichever applies) is also calculated (COUNT) for all selected survey days that have count data available for the stated time period. Then, the average count is divided by the average trip rate parameter value, and multiplied by the stated calculation factor (shown just above the table and abbreviated here as FACT). So, the method is: COUNT/TRP*FACT. Trip rates are then rounded to 3 decimal places.

TRICS 7.9.2

TRIP RATE for Land Use 07 - LEISURE/I - ART

GALLERIES/MUSEUMS/EXHIBITIONS

Calculation Factor: 100 sqm Count Type: TOTAL VEHICLES

			ARRIVALS			DEPAR S	TURE	Ave	TOTAL S
	No.	Ave.	Trip	No.	Ave.	Trip	No.	. Ave	Trip
Time Range	Days	GFA	Rate	Days	GFA	Rate	Days	GFA	Rate
00:00-01:00									
01:00-02:00									
02:00-03:00									
03:00-04:00									
04:00-05:00									
05:00-06:00									
06:00-07:00									
07:00-08:00									
08:00-09:00									
09:00-10:00	1	750	0.267	1	750	0.133	1	750	0.4
10:00-11:00	1	750	0	1	750	0.133	1	750	0.133
11:00-12:00	1	750	0	1	750	0	1	750	0
12:00-13:00	1	750	0.133	1	750	0	1	750	0.133
13:00-14:00	1	750	0.133	1	750	0.133	1	750	0.266
14:00-15:00	1	750	0.4	1	750	0.267	1	750	0.667
15:00-16:00	1	750	0.533	1	750	0.267	1	750	8.0
16:00-17:00	1	750	0.133	1	750	0.667	1	750	8.0
17:00-18:00	1	750	0	1	750	0.133	1	750	0.133
18:00-19:00									
19:00-20:00									
20:00-21:00									
21:00-22:00									
22:00-23:00									
23:00-24:00									
Daily Trip Rates:			1.599			1.733			3.332

TRICS 7.9.2

TRIP RATE for Land Use 07 - LEISURE/I - ART

GALLERIES/MUSEUMS/EXHIBITIONS

Calculation Factor: 100 sqm
Count Type: VEHICLE OCCUPANTS

			ARRIVALS			DEPAR S	TURE		TOTAL S
								Ave	
	No.	Ave.	Trip	No.	Ave.	Trip	No.		Trip
Time Range	Days	GFA	Rate	Days	GFA	Rate	Days	GFA	Rate
00:00-01:00									
01:00-02:00									
02:00-03:00									
03:00-04:00									
04:00-05:00									
05:00-06:00									
06:00-07:00									
07:00-08:00									
08:00-09:00									
09:00-10:00	1	750	0.267	1	750	0.133	1	750	0.4
10:00-11:00	1	750	0	1	750	0.133	1	750	0.133
11:00-12:00	1	750	0	1	750	0	1	750	0
12:00-13:00	1	750	0.133	1	750	0	1	750	0.133
13:00-14:00	1	750	0.267	1	750	0.133	1	750	0.4
14:00-15:00	1	750	0.533	1	750	0.533	1	750	1.066
15:00-16:00	1	750	0.933	1	750	0.533	1	750	1.466
16:00-17:00	1	750	0.133	1	750	0.8	1	750	0.933
17:00-18:00	1	750	0	1	750	0.133	1	750	0.133
18:00-19:00									
19:00-20:00									
20:00-21:00									
21:00-22:00									
22:00-23:00									
23:00-24:00									
Daily Trip Rates:			2.266			2.398			4.664

TRICS 7.9.2

TRIP RATE for Land Use 07 - LEISURE/I - ART

GALLERIES/MUSEUMS/EXHIBITIONS

Calculation Factor: 100 sqm Count Type: PEDESTRIANS

			ARRIVALS			DEPAR S	TURE	Ave	TOTAL S
	No.	Ave.	Trip	No.	Ave.	Trip	No.		Trip
Time Range	Days	GFA	Rate	Days	GFA	Rate	Days	GFA	Rate
00:00-01:00									
01:00-02:00									
02:00-03:00									
03:00-04:00									
04:00-05:00									
05:00-06:00									
06:00-07:00									
07:00-08:00									
08:00-09:00									
09:00-10:00	1	750	0	1	750	0	1	750	0
10:00-11:00	1	750	0.4	1	750	0.4	1	750	8.0
11:00-12:00	1	750	0	1	750	0	1	750	0
12:00-13:00	1	750	0	1	750	0	1	750	0
13:00-14:00	1	750	0.4	1	750	0.133	1	750	0.533
14:00-15:00	1	750	0	1	750	0	1	750	0
15:00-16:00	1	750	0	1	750	0.267	1	750	0.267
16:00-17:00	1	750	0	1	750	0	1	750	0
17:00-18:00	1	750	0	1	750	0	1	750	0
18:00-19:00									
19:00-20:00									
20:00-21:00									
21:00-22:00									
22:00-23:00									
23:00-24:00									
Daily Trip Rates:			0.8			0.8			1.6

TRICS 7.9.2

TRIP RATE for Land Use 07 - LEISURE/I - ART

GALLERIES/MUSEUMS/EXHIBITIONS

Calculation Factor: 100 sqm Count Type: TOTAL PEOPLE

			ARRIVALS			DEPAR S	TURE		TOTAL S
								Ave	
	No.	Ave.	Trip	No.	Ave.	Trip	No.	•	Trip
Time Range	Days	GFA	Rate	Days	GFA	Rate	Days	GFA	Rate
00:00-01:00									
01:00-02:00									
02:00-03:00									
03:00-04:00									
04:00-05:00									
05:00-06:00									
06:00-07:00									
07:00-08:00									
08:00-09:00									
09:00-10:00	1	750	0.267	1	750	0.133	1	750	0.4
10:00-11:00	1	750	0.4	1	750	0.533	1	750	0.933
11:00-12:00	1	750	0	1	750	0	1	750	0
12:00-13:00	1	750	0.133	1	750	0	1	750	0.133
13:00-14:00	1	750	0.667	1	750	0.267	1	750	0.934
14:00-15:00	1	750	0.533	1	750	0.533	1	750	1.066
15:00-16:00	1	750	0.933	1	750	0.8	1	750	1.733
16:00-17:00	1	750	0.133	1	750	8.0	1	750	0.933
17:00-18:00	1	750	0	1	750	0.133	1	750	0.133
18:00-19:00									
19:00-20:00									
20:00-21:00									
21:00-22:00									
22:00-23:00									
23:00-24:00									
Daily Trip Rates:			3.066			3.199			6.265

TRICS 7.9.2

TRIP RATE for Land Use 07 - LEISURE/I - ART

GALLERIES/MUSEUMS/EXHIBITIONS

Calculation Factor: 100 sqm

Count Type: CARS

			ARRIVALS			DEPAR S	TURE		TOTAL S
								Ave	
	No.	Ave.	Trip	No.	Ave.	Trip	No.		Trip
Time Range	Days	GFA	Rate	Days	GFA	Rate	Days	GFA	Rate
00:00-01:00									
01:00-02:00									
02:00-03:00									
03:00-04:00									
04:00-05:00									
05:00-06:00									
06:00-07:00									
07:00-08:00									
08:00-09:00									
09:00-10:00	1	750	0.267	1	750	0.133	1	750	0.4
10:00-11:00	1	750	0	1	750	0.133	1	750	0.133
11:00-12:00	1	750	0	1	750	0	1	750	0
12:00-13:00	1	750	0.133	1	750	0	1	750	0.133
13:00-14:00	1	750	0.133	1	750	0.133	1	750	0.266
14:00-15:00	1	750	0.4	1	750	0.267	1	750	0.667
15:00-16:00	1	750	0.533	1	750	0.267	1	750	8.0
16:00-17:00	1	750	0.133	1	750	0.667	1	750	8.0
17:00-18:00	1	750	0	1	750	0.133	1	750	0.133
18:00-19:00									
19:00-20:00									
20:00-21:00									
21:00-22:00									
22:00-23:00									
23:00-24:00									
Daily Trip Rates:			1.599			1.733			3.332

TRICS 7.9.2

Mode split

Mode	Total number of trips	Mode split
Taxis	0	0.0%
OGVs	0	0.0%
PSVs	0	0.0%
LGVs	0	0.0%
Cars	7	34.7%
Cyclists	0	0.0%
Pedestrians	13	65.3%
Bus	0	0.0%
Rail	0	0.0%
Motorcycles	0	0.0%
Total	20	100.0%

Total people

Calculation factor: 100sqm

Calculation facto		AR	RIVALS			[DEPARTURES			TOT	ΓALS	
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for	No. Days2	Ave. GFA3	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA4	Trip Rate2	Trip Rate2
00:00-01:00												
01:00-02:00												
02:00-03:00												
03:00-04:00												
04:00-05:00												
05:00-06:00												
06:00-07:00												
07:00-08:00				0				0				0
08:00-09:00				0				0				0
09:00-10:00	:	1 75	0 0.267	1		1 75	0.133	0		1 75	0 0.4	1
10:00-11:00		1 75	0 0.4	1		1 75	0.533	1		1 75	0.933	2
11:00-12:00		1 75	0 0	0		1 75	0 0	0		1 75	0 0	0
12:00-13:00		1 75	0 0.133	0		1 75	0 0	0		1 75	0.133	0
13:00-14:00		1 75	0 0.667	1		1 75	0.267	1		1 75	0.934	2
14:00-15:00		1 75	0 0.533	1		1 75	0.533	1		1 75	0 1.066	2
15:00-16:00		1 75	0.933	2		1 75	0.8	2		1 75	0 1.733	4
16:00-17:00		1 75	0 0.133	0		1 75	0.8	2		1 75	0.933	2
17:00-18:00		1 75	0 0	0		1 75	0.133	0		1 75	0.133	0
18:00-19:00				0				0				0
19:00-20:00												
20:00-21:00												
21:00-22:00												
22:00-23:00												
23:00-24:00												
Daily Trip Rates:			3.066	6			3.199	7			6.265	13

100sqm

Total proposed floorspace (sqm) 209

conversion factor

2.09

Total vehicles

Calculation factor: 100sqm

			ARRIVALS			[DEPARTURES		TOTALS				
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA3	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA4	Trip Rate2	Trip Rate2	
00:00-01:00													
01:00-02:00													
02:00-03:00													
03:00-04:00													
04:00-05:00													
05:00-06:00													
06:00-07:00													
07:00-08:00				()			C)			0	
08:00-09:00				(D			C				0	
09:00-10:00		1 750	0 0.267	1	L	1 75	0 0.133	C)	1 75	0 0.4	1	
10:00-11:00		1 750	0 0	()	1 75	0 0.133	C)	1 75	0 0.133	0	
11:00-12:00		1 75	0 0	()	1 75	0 0	C)	1 75	0 0	0	
12:00-13:00		1 750	0.133	()	1 75	0 0	C)	1 75	0 0.133	0	
13:00-14:00		1 75	0.133	()	1 75	0 0.133	C)	1 75	0 0.266	5 1	
14:00-15:00		1 75	0 0.4	1	L	1 75	0 0.267	1		1 75	0 0.667	1	
15:00-16:00		1 750	0.533	1	L	1 75	0 0.267	1		1 75	0 0.8	2	
16:00-17:00		1 75	0.133	()	1 75	0 0.667	1		1 75	0 0.8	2	
17:00-18:00		1 75	0 0	(1 75	0 0.133	C)	1 75	0 0.133	0	
18:00-19:00				()			C)			0	
19:00-20:00													
20:00-21:00													
21:00-22:00													
22:00-23:00													
23:00-24:00													
Daily Trip Rates:			1.599	3	3		1.733	4	L The state of the		3.332	7	

Total proposed 209 floorspace (sqm)

100sqm

conversion 2.09

Taxis

Calculation factor: 100sqm

Carcaration races			ARRIVALS			D	EPARTURES		TOTALS			
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA3	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA4 Trip Rate	2 Trip rate for site22	
00:00-01:00												
01:00-02:00												
02:00-03:00												
03:00-04:00												
04:00-05:00												
05:00-06:00												
06:00-07:00												
07:00-08:00				C)			0)		C	
08:00-09:00				C				0			C	
09:00-10:00				C)			0)		C	
10:00-11:00				C)			0)		C	
11:00-12:00				C)			0)		C	
12:00-13:00				C)			0)		C	
13:00-14:00				C)			0)		C	
14:00-15:00				C)			0)		C	
15:00-16:00				C)			0)		C	
16:00-17:00				C)			0)		0	
17:00-18:00				C)			0)		C	
18:00-19:00				C)			0)		C	
19:00-20:00												
20:00-21:00												
21:00-22:00												
22:00-23:00												
23:00-24:00												
Daily Trip Rates:				C)			0)		0	

Total proposed 209 floorspace (sqm)

100sqm

conversion 2.09

Vehicle occupants

Calculation factor: 100sqm

Carculation facto			ARRIVALS			[DEPARTURES		TOTALS				
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA3	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA4	Trip Rate2	Trip Rate2	
00:00-01:00													
01:00-02:00													
02:00-03:00													
03:00-04:00													
04:00-05:00													
05:00-06:00				()			C)			0	
06:00-07:00				()			C)			0	
07:00-08:00				()			C)			0	
08:00-09:00				(C)			0	
09:00-10:00		1 750	0 0.267	1	L	1 75	0 0.133	C)	1 75	0 0.4	1	
10:00-11:00		1 750	0 0	()	1 75	0 0.133	C)	1 75	0 0.133	0	
11:00-12:00		1 75	0 0	()	1 75	0 0	C)	1 75	0 0	0	
12:00-13:00		1 750	0.133	()	1 75	0 0	0)	1 75	0 0.133	0	
13:00-14:00		1 75	0.267	1	L	1 75	0 0.133	C)	1 75	0 0.4	1	
14:00-15:00		1 75	0.533	1	L	1 75	0 0.533	1		1 75	0 1.066	5 2	
15:00-16:00		1 75	0.933	2	2	1 75	0 0.533	1		1 75	0 1.466	3	
16:00-17:00		1 75	0.133	()	1 75	0 0.8	3		1 75	0 0.933	2	
17:00-18:00		1 75	0 0	(1 75	0 0.133	C		1 75	0 0.133	0	
18:00-19:00				(<mark>)</mark>			C)			0	
19:00-20:00				()			C)			0	
20:00-21:00				()			C)			0	
21:00-22:00													
22:00-23:00													
23:00-24:00													
Daily Trip Rates:			2.266	5	5		2.398	5			4.664	10	

Total proposed 209 floorspace (sqm)

100sqm

conversion 2.09

Cars

Calculation factor: 100sqm

			ARRIVALS			[DEPARTURES		TOTALS				
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA3	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA4	Trip Rate2	Trip rate for site3	
00:00-01:00													
01:00-02:00													
02:00-03:00													
03:00-04:00													
04:00-05:00													
05:00-06:00				0				()			0	
06:00-07:00				0				()			0	
07:00-08:00				0				()			0	
08:00-09:00				0				()			0	
09:00-10:00		1 75	0.267	1		1 75	0 0.133	3)	1 75	0 0.4	1	
10:00-11:00		1 75	0 0	1		1 75	0 0.133	3)	1 75	0.133	0	
11:00-12:00		1 75	0 0	1		1 75	0 (0)	1 75	0 0	0	
12:00-13:00		1 75	0.133	1		1 75	0 (0)	1 75	0.133	0	
13:00-14:00		1 75	0.133	1		1 75	0 0.133	3)	1 75	0.266	1	
14:00-15:00		1 75	0.4	1		1 75	0 0.267	7		1 75	0.667	1	
15:00-16:00		1 75	0.533	1		1 75	0 0.267	7		1 75	0.8	2	
16:00-17:00		1 75	0.133	1		1 75	0.667	7		1 75	0.8	2	
17:00-18:00		1 75	0 0	1		1 75	0 0.133	3)	1 75	0.133	0	
18:00-19:00				0				()			0	
19:00-20:00				0				()			0	
20:00-21:00				0				()			0	
21:00-22:00													
22:00-23:00													
23:00-24:00													
Daily Trip Rates:			1.599	3			1.733	3			3.332	7	

Total proposed 209 floorspace (sqm)

100sqm

conversion 2.09

Pedestrians

Calculation factor: 100sqm

Carcalation factors 2003qm			ARRIVALS			[DEPARTURES		TOTALS				
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA2	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA3	Trip Rate2	Trip rate for site3	
00:00-01:00													
01:00-02:00													
02:00-03:00													
03:00-04:00													
04:00-05:00													
05:00-06:00													
06:00-07:00													
07:00-08:00				0				()			0	
08:00-09:00				0				()			0	
09:00-10:00		1 75	50	0		1 75	50	0)	1 75	0 0.4	1	
10:00-11:00		1 75	0.4	1		1 75	0 0	.4 1	-	1 75	0 0.933	2	
11:00-12:00		1 75	50	0		1 75	50	0	<mark>)</mark>	1 75	0 0	0	
12:00-13:00		1 75	50	0		1 75	50	0	<mark>)</mark>	1 75	0 0.133	0	
13:00-14:00		1 75	0.4	1 1		1 75	0.13	33 ()	1 75	0 0.934	. 2	
14:00-15:00		1 75	50	0		1 75	50	0	<mark>)</mark>	1 75	0 1.066	2	
15:00-16:00		1 75	50	0		1 75	0.26	57 <u> </u>	_	1 75	0 1.733	4	
16:00-17:00		1 75	60	0		1 75	50	0	<mark>)</mark>	1 75	0 0.933	2	
17:00-18:00		1 75	60	0		1 75	50	0		1 75	0 0.133	0	
18:00-19:00				0				(<mark>)</mark>			0	
19:00-20:00													
20:00-21:00													
21:00-22:00													
22:00-23:00													
23:00-24:00													
Daily Trip Rates:			0.8	3 2			0	.8 2	2		6.265	13	

Total proposed floorspace (sqm) 209

100sqm 2.09

OGVs

Calculation factor: 100sqm

Calculation facto			ARRIVALS			E	EPARTURES		TOTALS			
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA3	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA4	Trip Rate2	Trip rate for site3
00:00-01:00												
01:00-02:00												
02:00-03:00												
03:00-04:00												
04:00-05:00												
05:00-06:00												
06:00-07:00												
07:00-08:00				0				0				0
08:00-09:00				0				0				0
09:00-10:00				0				0				0
10:00-11:00				0				0				0
11:00-12:00				0				0				0
12:00-13:00				0				0				0
13:00-14:00				0				0				0
14:00-15:00				0				0				0
15:00-16:00				0				0				0
16:00-17:00				0				0)			0
17:00-18:00				0				0				0
18:00-19:00				0				0				0
19:00-20:00												
20:00-21:00												
21:00-22:00												
22:00-23:00												
23:00-24:00												
Daily Trip Rates:				0				0				0

Total proposed 209 floorspace (sqm)

100sqm

conversion 2.09

PSVs

Calculation factor: 100sqm

			ARRIVALS			E	EPARTURES		TOTALS				
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA3	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA4	Trip Rate2	Trip rate for site3	
00:00-01:00													
01:00-02:00													
02:00-03:00													
03:00-04:00													
04:00-05:00													
05:00-06:00													
06:00-07:00													
07:00-08:00				0				()			0	
08:00-09:00				0				()			0	
09:00-10:00				0				()			0	
10:00-11:00				0				()			0	
11:00-12:00				0				()			0	
12:00-13:00				0				()			0	
13:00-14:00				0				()			0	
14:00-15:00				0				()			0	
15:00-16:00				0				()			0	
16:00-17:00				0				()			0	
17:00-18:00				0				()			0	
18:00-19:00				0				()			0	
19:00-20:00													
20:00-21:00													
21:00-22:00													
22:00-23:00													
23:00-24:00													
Daily Trip Rates:				0			(0)			0	

Total proposed 209 floorspace (sqm)

100sqm

conversion 2.09

LGVs

Calculation factor: 100sqm

Calculation facto			ARRIVALS			E	DEPARTURES		TOTALS			
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA3	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA4	Trip Rate2	Trip rate for site3
00:00-01:00												
01:00-02:00												
02:00-03:00												
03:00-04:00												
04:00-05:00												
05:00-06:00				0				0				0
06:00-07:00				0				0				0
07:00-08:00				0				0				0
08:00-09:00				0				0				0
09:00-10:00				0				0				0
10:00-11:00				0				0				0
11:00-12:00				0				0				0
12:00-13:00				0				0				0
13:00-14:00				0				0				0
14:00-15:00				0				0				0
15:00-16:00				0				0				0
16:00-17:00				0				0				0
17:00-18:00				0				0				0
18:00-19:00				0				0				0
19:00-20:00				0				0				0
20:00-21:00				0				0				0
21:00-22:00												
22:00-23:00												
23:00-24:00												
Daily Trip Rates:				0				0				0

Total proposed 209 floorspace (sqm)

100sqm

conversion 2.09

Bus passengers

Calculation factor: 100sqm

Calculation facto			ARRIVALS			[DEPARTURES				TOTALS	
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA2	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA3	Trip Rate2	Trip rate for site3
00:00-01:00												
01:00-02:00												
02:00-03:00												
03:00-04:00												
04:00-05:00												
05:00-06:00												
06:00-07:00												
07:00-08:00				0				C				0
08:00-09:00				0				C				0
09:00-10:00				0				C				0
10:00-11:00				0				C				0
11:00-12:00				0				C				0
12:00-13:00				0				C				0
13:00-14:00				0				C				0
14:00-15:00				0				C				0
15:00-16:00				0				C				0
16:00-17:00				0				C				0
17:00-18:00				0				C				0
18:00-19:00				0				C				0
19:00-20:00												
20:00-21:00												
21:00-22:00												
22:00-23:00												
23:00-24:00												
Daily Trip Rates:				0				C				0

Total proposed floorspace (sqm) 100sqm

conversion 0

Cyclists

Calculation factor: 100sqm

			ARRIVALS			[DEPARTURES		TOTALS			
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA3	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA4	Trip Rate2	Trip rate for site3
00:00-01:00												
01:00-02:00												
02:00-03:00												
03:00-04:00												
04:00-05:00												
05:00-06:00				0				C)			0
06:00-07:00				0				C)			0
07:00-08:00				0				C)			0
08:00-09:00				0				C)			0
09:00-10:00				0				C)			0
10:00-11:00				0				C)			0
11:00-12:00				0				C)			0
12:00-13:00				0				C)			0
13:00-14:00				0				C)			0
14:00-15:00				0				C)			0
15:00-16:00				0				C)			0
16:00-17:00				0				C)			0
17:00-18:00				0				C)			0
18:00-19:00				0				C)			0
19:00-20:00				0				C)			0
20:00-21:00				0				C)			0
21:00-22:00												
22:00-23:00												
23:00-24:00												
Daily Trip Rates:				0				C	•			0

Total proposed 209 floorspace (sqm)

100sqm

conversion 2.09

Motorcyclists

Calculation factor: 100sqm

Calculation facto			ARRIVALS			[DEPARTURES				TOTALS	
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA2	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA3	Trip Rate2	Trip rate for site3
00:00-01:00												
01:00-02:00												
02:00-03:00												
03:00-04:00												
04:00-05:00												
05:00-06:00				0)			()			0
06:00-07:00				0)			()			0
07:00-08:00				0))			0
08:00-09:00				0				(0
09:00-10:00				0)			()			0
10:00-11:00				0)			()			0
11:00-12:00				0))			0
12:00-13:00				0)			()			0
13:00-14:00				0)			()			0
14:00-15:00				0)			()			0
15:00-16:00				0))			0
16:00-17:00				0))			0
17:00-18:00				0				(0
18:00-19:00				0)			()			0
19:00-20:00				0))			0
20:00-21:00				0)			()			0
21:00-22:00												
22:00-23:00												
23:00-24:00												
Daily Trip Rates:				0)			0

Total proposed 209 floorspace (sqm)

100sqm

conversion 2.09

Rail passengers

Calculation factor: 100sqm

Calculation facto	1		ARRIVALS			[DEPARTURES				TOTALS	
Time Range	No. Days	Ave. GFA	Trip Rate	Trip rate for site	No. Days2	Ave. GFA2	Trip Rate3	Trip rate for site2	No. Days3	Ave. GFA3	Trip Rate2	Trip rate for site3
00:00-01:00												
01:00-02:00												
02:00-03:00												
03:00-04:00												
04:00-05:00												
05:00-06:00												
06:00-07:00												
07:00-08:00				0)				O			0
08:00-09:00				0				(D			0
09:00-10:00				0)			(O			0
10:00-11:00				0)			(0			0
11:00-12:00				0)				O			0
12:00-13:00				0)			()			0
13:00-14:00				0)			(O			0
14:00-15:00				0)			(0			0
15:00-16:00				0)			(0			0
16:00-17:00				0)				0			0
17:00-18:00				0				(D			0
18:00-19:00				0)			()			0
19:00-20:00												
20:00-21:00												
21:00-22:00												
22:00-23:00												
23:00-24:00												
Daily Trip Rates:				0)			0

Total proposed floorspace (sqm) 100sqm

conversion 0

Cambridge Waste Water Treatment Relocation Project Transport Assessment



Appendix I: MCC and ATC comparisons

Cambridge Waste Water Treatment Relocation Project Appendix I 5.4.19.13



Document Control

Document title	5.4.19.13 ATC to MCC Comparison
Version No.	1
Date Approved	17 October 2022
Date 1st Issued	

Version History

Version	Date	Author	Checked	Approved	Description of change
1				_	Final

Cambridge Waste Water Treatment Relocation Project Appendix I 5.4.19.13



Contents

1	Site	s surveyed	1
	1.1	Overview	1
	1.2	ATC Site – Denny End Road	2
	1.3	ATC Site 2 – Car Dyke Road	3
	1.4	ATC Site 3 – Clayhithe Road	3
	1.5	ATC Site 4 – Clayhithe Road	3
	1.6	ATC Site 5 – Horningsea Road	4
	1.7	ATC Site 6 - Milton Road	4
	1.8	ATC Site 7 – Fen Road	4
	1.9	ATC Site 8 – Green End Road	4
	1.10	ATC Site 9 – Water Street	5
T	ables		
Ta	able 1.:	1: Summary of sites surveyed	1



1 Sites surveyed

1.1 Overview

Table 1.1: Summary of sites surveyed

Site	Road name	%	Summary
number		difference	
Site 1	Denny End Road	8.0%	ATC is around 8% higher than MCC counts in both AM and PM peak. A possible explanation for the higher ATC figures than MCC is that the ATC captures traffic accessing and egressing the construction site access point along Denny End Lane at the Cambridgeshire Army Cadets Force from the Waterbeach direction whereas the MCC does not as the MCC is placed at the A10/Denny End Lane junction. Traffic could choose to egress from the construction site by turning left as there are queues on the right hand turn towards the A10 from the site construction access point and the MCC would not capture this movement.
Site 2	Car Dyke Road	1.1%	MCC is 10% higher than ATC in AM Peak, However ATC is 7% higher than MCC in the PM peak
Site 3	Clayhithe Road	Comparable location not available	N/A
Site 4	Bannold Road	3.5%	ATC is 2% higher than MCC in AM Peak and around 5% higher in the PM peak
Site 5	Horningsea Road	1.0%	MCC is around 109% higher than ATC counts in AM peak and 91% higher in PM peak
Site 6	Miltom Road	0.4%	MCC is 4% higher than ATC counts in AM peak, however ATC is 3% higher in PM peak
Site 7	Fen Road	Comparable location not available	N/A
Site 8	Green End Road	3.1%	MCC is 11% higher than ATC counts in AM peak, however ATC is 5% higher in PM peak
Site 9	Water Street	10.5%	MCC is around 14% higher than ATC counts in AM peak and around 8% higher in PM peak
Average		3.9%	



1.2 ATC Site – Denny End Road

	3-day Average (Tue-Thur)			Summary
	Percentage		•	ATC is around 8% higher than MCC counts in both AM and PM peak.
	ATC	MCC	Difference	A possible explanation for the higher ATC figures than MCC is that
7000-1000	1472	1359	8.3%	the ATC captures traffic accessing and egressing the construction site access point along Denny End Lane at the Cambridgeshire Army
1600-1800	1494	1388	7.6%	Cadets Force from the Waterbeach direction whereas the MCC does not as the MCC is placed at the A10/Denny End Lane junction. Traffic could choose to egress from the construction site by turning left as there are queues on the right hand turn towards the A10 from the site construction access point and the MCC would not capture this
Total	2966	2747	8.0%	movement.

ATC Site 1 location





ATC location



MCC location





1.3 ATC Site 2 – Car Dyke Road

	3-day	Averag	e (Tue-Thur)	Summary
	ATC	MCC	Percentage difference	MCC is 10% higher than ATC in AM
7000-1000	1067	1176	10.2%	Peak, However ATC is 7% higher
1600-1800	1205	1121	7.4%	than MCC in the PM peak
Total	2272	2297	1.1%	

1.4 ATC Site 3 – Clayhithe Road

3-day Average (Tue-Thur)

	ATC	MCC	Percentage difference				
7000-1000	908		NA				
1600-1800	1025		NA				
Total	1933	0	Comparable location not available				

1.5 ATC Site 4 – Clayhithe Road

	3-day	Averag	ge (Tue-Thur)	Summary
	ATC	MCC	Percentage difference	ATC is 2% higher than MCC in AM
7000-1000	628	615	2.1%	
1600-1800	722	689	4.7%	PM peak
Total	1350	1304	3.5%	



1.6 ATC Site 5 – Horningsea Road

	3-day Average (Tue-Thur)			Summary
	ATC	MCC	Percentage difference	MCC is around 109% higher than ATC counts in AM peak and 91% higher in PM peak
7000-1000	1108	1147	3.5%	
1600-1800	1206	1144	5.4%	
Total	2314	2291	1.0%	

1.7 ATC Site 6 - Milton Road

3-day Average (Tue-Thur)				Summary
	ATC	MCC	Percentage difference	MCC is 4% higher than ATC
7000-1000	4369	4542	4.0%	counts in AM peak, however
1600-1800	4269	4132	3.3%	ATC is 3% higher in PM peak
Total	8639	8674	0.4%	

1.8 ATC Site 7 – Fen Road

- 1	_			
3-d	av Av	erage	lTue-T	hur)

	3 day Average	, (rac mar)	
	ATC (Fen Road)	MCC (Water Lane)	Percentage Difference
7000-1000	521		
1600-1800	600		
Total	1121		Comparable location not available

1.9 ATC Site 8 – Green End Road

	3-day Average (Tue-	-Thur)	Summary		
	ATC (Green End Road)	MCC (Green End Road) (NE)	Percentage Difference	MCC is 11% higher than ATC counts in	
7000- 1000	1848	2055	11.2%	AM peak, however	
1600- 1800	1862	1768	5.3%	ATC is 5% higher in PM peak	
Total	3710	3823	3.1%		

Cambridge Waste Water Treatment Relocation Project Appendix I 5.4.19.13



1.10 ATC Site 9 – Water Street

	3-day A	verage (Tue-1	「hur)	Summary
	ATC (Water Street)	MCC (Site 20 Water Lane) (SE)	Percentage difference	MCC is around 14% higher than ATC counts in AM peak and around 8% higher in PM peak
7000- 1000	998	1135	13.7%	nigher in Pivi peak
1600- 1800	1100	1183	7.6%	
Total	2098	2318	10.5%	

Cambridge Waste Water Treatment Relocation Project Transport Assessment




Appendix J: Consultation 2 Stakeholder Feedback

Cambridge Waste Water Treatment Relocation Project Appendix J: Consultation 2 stakeholder feedback




Date	Consultee	Points raised	How and where addressed
18/08/21	Cambridge Past, Present & Future (CPPF)	The main area of uncertainty is the vehicle access. CPPF strongly objects to any proposals to provide vehicular access into the site from the farm access bridge at Honey Hill via Junction 35 (Option 2).	Option 2 was not selected, the access within the Proposed Development is Option 1b, which does not interact directly with Junction 35. The selection of vehicle access and consideration of all options is discussed further within Chapter 3: Site Selection and Alternatives (Application Document Reference 5.2.3). The assessment provided in Section 4 (Assessment of Effects) of this chapter assesses Option 1b.
12 August 2021	National Highways	Access option 1a remains National Highways' preferred option, closely followed by Option 1b. Access option 3 would be contrary to policy 'The Strategic Road Network and the delivery of sustainable development' and therefore National Highways object to this proposal.	Option 3 has not been selected on account of technical issues around creating a new junction off the A14 based on National Highways' feedback – the access is Option 1b. The selection of vehicle access and consideration of all options is discussed in further within Chapter 3: Alternatives Considered. The assessment provided in Section 4 (Assessment of Effects) of this chapter assesses Option 1b.
12 August 2021	National Highways	The TA should also consider any other development that makes up part of the application, such as the proposed recreation facilities.	Noted and accepted. The Transport Assessment Application Document Reference 5.4.19.3) covers all aspects of Proposed Development, including the proposed visitor centre.
13 August 2021	East Cambridge District Council	Most acceptable options are options 1a and 1b. To create an additional access from the A14 is unlikely to be acceptable.	The preferred access option is Option 1b.
18 August 2021	Urban and Civic	U&C offers a preliminary view that a new junction off the A14 appears, without the benefit of the detailed assessments that will follow, to be preferrable and justified given the strategic importance of the proposed facility.	Noted. Option 3 has not been selected on account of technical issues around creating a new junction off the A14 based feedback provided by National Highways— the access is Option 1b. The selection of vehicle access and consideration of all options is discussed in further detail within Chapter 3: Site Selection and Alternatives (Application Document Reference 5.2.3). The assessment provided in Section 4 (Assessment of Effects) of this chapter assesses Option 1b.
16 August 2021	Natural England	Access assessment needs to include air quality assessment. A CEMP is also needed.	Noted. An air quality assessment has been undertaken as part of Chapter 7: Air Quality (Application Document Reference 5.2.7). The CoCP Part A and B (Application Document Reference. 5.4.2.1, 5.4.2.2) requires a CEMP to be produced prior to any works commencing on site.





Date	Consultee	Points raised	How and where addressed
17 August 2021	Cambridgeshire County Council	junction will operate within capacity. This is subject to further work on the flows and so is the preliminary findings	Noted and accepted. As stated, Junction 34 of the A14 has been modelling in accordance with CCC requirements, whereby preliminary findings show that the junction works within capacity. The Transport Assessment (Application Document Reference. 5.4.19.3) includes information on modelling during construction, operation (including visitor traffic) and decommissioning. Mitigation proposals and drawings for Horningsea Road have taken into account the Horningsea Greenway project.
17 August 2021	South Cambridge District Council	If Option 1b remains, the District Council will expect to see within the DCO, carefully detailed designs for the junction and details of control systems to prevent vehicles travelling to and from the site using any access routes other than the A14 during the construction and operation stages. Given the rationale presented by Anglian Water for the choice of Option 1b, the District Council's recommendation again if this remains the proposed option, it should also deliver enhanced pedestrian and cycle access, cycling facilities. Importantly, details indicating how access to the site would not compromise cycling safety along Horningsea Road, in the vicinity of the new junction/4th arm will be required as part of the DCO. In addition, the District Council considers that measures to avoid traffic queuing/congestion on Denny End Road and Bannold Road need to be incorporated into the DCO proposals as this route is prone to congestion. The District Council remains of the opinion that direct access from the A14 would be the preferred option rather than Option 1b and asks Anglian Water to reconsider.	Option 1b-has been selected and taken forward into the Proposed Development. Option 3 has not been selected on account of technical issues around creating a new junction off the A14 based on feedback provided by National Highways. The Transport Assessment (Application Document Reference 5.4.19.3) provides details on the mitigation measures on Horningsea Road, which is also summarised in the section 2.8 of this chapter. These mitigation measures ensure that access to the site does not compromise safety along Horningsea Road The Transport Assessment Application Document Reference. 5.4.19.3) includes a review of the junctions with the A10 / Denny End Road and A10 / Car Dyke Lane to assess capacity and delay during the construction works. Bannold Road at its junction with Denny End Road is noted as narrow (Application Document Reference. 5.4.19.3) and mitigation will be in place to prevent parking on that corner to minimise traffic conflicts. The CTMP (Application Document Reference. 5.4.19.7) and CoCP (Application Document Reference. 5.4.2.1, 5.4.2.2) set out the construction route to and from the proposed WWTP site.





Date	Consultee	Points raised	How and where addressed
17 August 2021	Fen Ditton Parish Council	FDPC considers extra mitigation is required and should include: • Commitment to model overall traffic performance with historic data as a baseline and not rely on AWS surveys since these were at a time when traffic into Cambridge was below historic levels.	The modelling approach and use of survey information has been discussed and agreed with CCC. This includes checks to ensure survey results provided by AWS are not abnormal due to the Covid-19 pandemic. The Transport Assessment (Application Document Reference 5.4.19.3) is supported by additional surveys completed to verify the data used.
24 August 2021	Horningsea Parish Council	HPC is not aware of any evaluation assessment material being published by AWS and would like to request this information to allow HPC a full understanding of the relevant facts. We also request a copy of the determination by Highways that found it was not possible to access the site from the A14, Option 3.	Chapter 3: Site Selection and Alternatives (Application Document Reference 5.2.3) provides details of the access options considered for the project. Option 3 has not been selected on account of technical issues around creating a new junction off the A14 based on feedback from National Highways.
24 August 2021	Horningsea Parish Council	We fear that the traffic volume has been underestimated. We would like to see this analysis including all of the access routes into the site; including A14 westbound and A14 eastbound.	The modelling approach and use of survey information has been discussed and agreed with CCC. This includes checks to ensure that survey results provided by AWS are not abnormal due to the Covid-19 pandemic. The Transport Assessment (Application Document Reference. 5.4.19.3) is supported by additional surveys completed to verify the data used.
24 August 2021	Horningsea Parish Council	HPC also supports reduced speed limits on Horningsea Road. Suggest reduce to 30mph and 20mph in the village and enforce with speed cameras and traffic calming measures. We also want confirmation that this mitigation is within the control of AWS.	A set of mitigation measures for Horningsea Road have been included in the design and are outlined in mitigation measures adopted as part of the Proposed Development.
24 August 2021	Horningsea Parish Council	It is a significant concern that we believe AWS has failed to factor in the cumulative traffic impact of previous recorded congestion at junction 34, reduction in traffic flows (due to Covid) during the 2021 AWS surveys, CWWTP Construction traffic, CWWTP operational traffic, the proposed additional J34 arm, Waterbeach New Town, Marleigh, development at Fulbourn, dualling of the A10, general traffic growth and the pending development of the airport site.	The modelling approach and use of survey information has been discussed and agreed with CCC. This includes checks to ensure survey results provided by the Applicant are not abnormal due to the Covid-19 pandemic. The Transport Assessment (Document Reference 5.4.19.3) is supported by additional surveys completed to verify the data used. Impacts associated with committed developments in the area are accounted for within the TEMPro growth factors used, which has been agreed with CCC.
24 August 2021	Horningsea Parish Council	We request forecast operational HGV movements. Most of the movements are liquid sludge imports and septic tank	The Transport Assessment (Application Document Reference. 5.4.19.3) provides information on operational HGV movements. The routing of

Cambridge Waste Water Treatment Relocation Project Appendix J: Consultation 2 stakeholder feedback



Date	Consultee	Points raised	How and where addressed
		movements, why are these being trucked here from	HGVs in operation has been based on sludge imports at the existing
		destinations such as Ely and Huntingdon? We request	Cambridge WWTP. A technical note (Appendix C, Application
		forecast for operational HGV movements and an alternativ	re Document Ref: 5.4.19.3) outlines the origins of sludge imports during
		plan for the movement of sludge lorries to more	operation in 2020 at the existing Cambridge WWTP.
		appropriate sites.	

Cambridge Waste Water Treatment Relocation Project Transport Assessment



Appendix K: TEMPro Growth Factor Technical Note

Cambridge Waste Water Treatment Relocation Project 5.4.19.3 – Appendix K



Document Control

Document title	Technical Note: Modelling Overview and TEMPro Growth Factor
Version No.	1
Date Approved	
Date 1st Issued	12/01/2022

Version History

Version	Date	Author	Description of change
0	12/01/2022	-	Technical note at PEI.
1	15/02/2024	-	Revisions to TEMPro growth factors
			following modelling review and
			formatting updates.

Cambridge Waste Water Treatment Relocation Project 5.4.19.3 – Appendix K



Contents

1	Ted	chnical Note: Modelling overview and TEMPro growth factors	. 3
	1.1	Preliminary Modelling Overview	. 3
	1.2	Survey and TEMPro growth factors	. 3
Т	able	S	
Ta	able 1	-1: TEMPro growth factors	. 3



1 Technical Note: Modelling overview and TEMPro growth factors

1.1 Preliminary Modelling Overview

- 1.1.1 Each option has been assessed using the industry-standard software of either Junctions 9 (PICADY) or LinSig (Version 3) to anticipate if the proposed junction designs would be predicted to operate within capacity.
- 1.1.2 Junctions9 software measures performance as the ratio of flow to capacity (RFC). An RFC value is greater than one means that a turning movement has a higher level of traffic flow than its theoretical capacity. As a result, queues may occur. An RFC below 0.85 is considered acceptable as there is still scoped to accommodate future growth.
- 1.1.3 LinSig is a computer software package for assessing and designing traffic signal junctions either individually or as a network comprised of several junctions. It is used by traffic engineers to construct a model of the junction or network which can then be used to assess different designs and methods of operation. LinSig v3 software measures performance as the degree of saturation (DoS). A DoS value of greater than 100% means that a lane movement has a higher level of traffic flow than its theoretical capacity. As a result, queues may occur. A DoS below 90% is considered acceptable as there is still coped to accommodate future growth.

1.2 Survey and TEMPro growth factors

1.2.1 Survey (December 2021) data has been used to inform the base years. To estimate the future 2025 base, a TEMPro 7.2 growth factors for South Cambridgeshire have been applied to the base flows. The applied factors are outlined in Table 1-1 below:

Table 1-1: TEMPro growth factors

Base Year to Scenario Year	TEMPro growth factors
2021 – 2026	1.060
2021 – 2028	1.082
2021 – 2033	1.1362
2021 – 2038	1.1857

1.2.2 To predict future growth as accurate as possible, TEMPro 7.2 reflects all planned growth in the area. TEMPro 7.2 growth factors are in line with the most recent Road Traffic Forecast (2018). However, as land use developments are a source of uncertainty, TEMPro 7.2 growth factors are blanket, and they do not predict where exactly growth will appear.

Cambridge Waste Water Treatment Relocation Project 5.4.19.3 – Appendix K



- 1.2.3 It is suggested to apply unadjusted growth factors to estimate the future base as the Cambridge Wastewater Treatment plant will not generate a significant number of homes or jobs in the area.
- 1.2.4 However, if any significant developments appear in the area, forecasted trips could be excluded from the growth to avoid double counting. In this case, the developments and the number of excluded trips should be agreed with CCC.